

## GREEN POWER GP1000SM-P SOUNDPROOF



Reference: 00913

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

### You can choose from several versions:

- Silenced group with AVR-Leroy alternator (automatic control pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	804
Continuous power three phase (KW)	732
Maximum power three phase (KVA)	1005
Continuous power three phase (KVA)	915
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Perkins 4008 TAG1A
Emissions Regulations	NON EMISSIONATO

Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	30561
Number cylinders	8
Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTEECO43 2S/4
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	650
Consumption (L/h)	142 al 75% del carico
Running time (h)	4.57 al 75% del carico
Acoustic pressure	72 dB(A)
Length (mm)	6500
Width (mm)	2270
Height (mm)	2550
Dry weight (Kg)	11100
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR