



GREEN POWER GP700A/C OPEN (MANUAL CONTROL UNIT)

Reference: 00928

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	560
Continuous power three phase (KW)	508.8
Maximum power three phase (KVA)	700
Continuous power three phase (KVA)	636
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	CUMMINSVTA28G5
Emissions Regulations	NON EMISSIONATO
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	28000
Number cylinders	12

Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTEECO40 2L/4
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	340
Consumption (L/h)	104 Lt/h al 75% del carico
Running time (h)	9.62 h al 75% del carico
Length (mm)	3500
Width (mm)	1600
Height (mm)	2100
Dry weight (Kg)	3430
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR