

GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

Reference: 00936 AVR-Mecc alte automatica



GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP1000A/C in its open design, equipped with a manual control unit for precise and hands-on operation. This model represents GREEN POWER's commitment to delivering performance with the advantage of manual control, ensuring flexibility and reliability in a variety of applications. Its open configuration allows for easy installation and maintenance, making it an essential tool for those demanding peak efficiency. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

""

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	800
Continuous power three phase (KW)	728
Maximum power three phase (KVA)	1000
Continuous power three phase (KVA)	910
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	CUMMINS KTA38G3

Emissions Regulations	Non Emissionati
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	37800
Number cylinders	12
Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTE ECO43 2S/4
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	400
Consumption (L/h)	24.7 Lt/h al 75% del carico
Running time (h)	2.64 h al 75% del carico
Length (mm)	
Width (mm)	2050
Height (mm)	2350
Dry weight (Kg)	3430
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR