



## GREEN POWER GP30SH/KW SOUNDPROOF

Reference: 00155-BM

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**QUESTO PRODOTTO È DISPONIBILE SOLO NELLA VERSIONE CON CENTRALINA AUTOMATICA**

**È possibile scegliere tra diverse versioni:**

- Gruppo silenziato con alternatore AVR-Leroy (centralina automatica)
- Gruppo silenziato con alternatore AVR-Mecc alto (centralina automatica)
- Gruppo silenziato con alternatore AVR-Stamford (centralina automatica)

The image is purely indicative.

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	22.9
Continuous power three phase (KW)	20.8
Maximum power three phase (KVA)	28.6
Continuous power three phase (KVA)	26
Fuel	Diesel
Frequency (Hz)	50

Voltage (V)	230 / 400
Engine	Kohler KDI 2504M
Emissions Regulations	STAGE 3A
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	2482
Number cylinders	4
Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTE ECP28-VL/4
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	70
Consumption (L/h)	1.9 al 75% del carico
Running time (h)	14.89 h al 75% del carico
Length (mm)	2100
Width (mm)	900
Height (mm)	1150
Dry weight (Kg)	705
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR