

## GREEN POWER GP2530A/M OPEN (MANUAL CONTROL UNIT)

Reference: 00871



The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	2024
Continuous power three phase (KW)	1840
Maximum power three phase (KVA)	2530
Continuous power three phase (KVA)	2300
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	MTU 16V 4000 G24F
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	76300
Number cylinders	16
Cylinders' position	In line

Cooling	Water
Alternator	MECC ALTE ECO46-1.5L/4
Poles	4
Fuel tank capacity (L)	800
Consumption (L/h)	427 Lt/h al 75% del carico
Running time (h)	1.87 h al 75% del carico
Length (mm)	6100
Width (mm)	2300
Height (mm)	3000
Dry weight (Kg)	12500
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Precision of voltage regulation	± 1%