



GENSET MG 4000 I-HE SINGLE PHASE GENERATOR 3,85 KVA

Reference: MG 4000 I-HE

GENSET MG 4000 I-HE SINGLEPHASE GENERATOR 3,85 KVA

The generator GENSET MG 4000 I-HE singlephase features a gasoline engine capable of delivering 3,85 KVA with voltage regulator.

The GENSET MG 4000 I-HE singlephase generator provides reliable power for home, work and recreation environments Safely powering appliances and other electronic devices solution for outdoor parties.

GENSET MG 4000 I-HE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the Honda OHV engine that allows to deliver a maximum power of 3.85 KVA.

The entire GENSET MG 4000 I-H range has successfully passed different tests for each component of which the groups and the final product itself are composed in order to give the best possible reliability to the user.

The strengths of the single-phase generator 3.85 KVA are: the high quality of components, lightness, compactness, portability and ease of use and also modern design. The 3.85 KVA single-phase generator is equipped with a manual rope starter.

TECHNICAL FEATURES GENSET MG 4000 I-H

Phase Type: SinglePhase
Maximum SinglePhase Output: 3.85 KVA
Maximum SinglePhase Output: 3.08 KW
VAC Voltage: 230 V
Frequency (Hz): 50
Starting Frame: Manual with self-winding
Motor: Honda GX 200 OHV
Emission Standard: Stage V
RPM: 3000
Supply: Gasoline
Fuel tank capacity: 3.1 l
Consumption @ 75 % load: 1.5 l/h
Autonomy @ 50 % load: 2.06 h
Sound pressure: 95 dB(A) @ 7m
Length: 610 mm
Width: 360 mm
Height: 410 mm
Net weight: 38 Kg

Looking for a generator with different characteristics? [Here](#) you can find the full range of generators GENSET or other specialized brands

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.08
Maximum power single phase (KVA)	3.85
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 Schuko
Engine	Honda GX200, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Ignition	Recoil
Starting system	Manual
Engine capacity (cm ³)	196
Number cylinders	1
Cooling	Air
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	3.1
Acoustic power	98 dB(A)
Acoustic pressure	73 dB(A) at 7 m
Length (mm)	610
Width (mm)	360
Height (mm)	410
Dry weight (Kg)	38
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	No

Engine manufacturer

Honda
