



GENMAC Daily-GAS RG4700HS LPG GENERATOR 5,9KVA

Reference: Daily-GAS RG4700HS LPG

GENMAC DAILY-GAS RG4700HS LPG SINGLE-PHASE GENERATOR 5,9KVA

The Genmac Daily-GAS RG4700HS LPG single phase generator is equipped with a Honda engine powered by LPG gas capable of delivering a power of 5.9KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced three-phase LPG power generator, Genmac with 5.9KVA power. The Genmac LPG generator is equipped with an oversized air-cooled Honda engine.

Genmac professional LPG generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Honda engines are built using the best materials, the most innovative techniques and the most advanced methods for quality control.

Each engine is thoroughly tested in order to prove its perfect functioning before delivery.
In case of need, Honda's assistance service is always at your disposal.

The 5.9KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily-GAS RG4700HS LPG 5,9KVA

Voltage regulator : capacitor (AVR Optional)
Power supply: Methane gas
Starting: Electric
Single-phase
Maximum Output: 4,9KW
Maximum output: 4,8KVA

Maximum Output: 4,8KW
Maximum Output: 5,3KVA
Voltage: 230V
Frequency: 50 Hz
3000 revolutions per minute
Autonomy @ 75%: 1.7 h fixed revolutions
Length (mm): 1030
Width (mm): 620
Height (mm): 804
Dry weight (Kg): 210

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.3
Continuous power single phase (KW)	4.7
Maximum power single phase (KVA)	5.9
Continuous power single phase (KVA)	5.2
Fuel	LPG
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 16A 230V / 2 x 32A 230V
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Cooling	Air
Poles	2
Consumption (L/h)	1.7 mc. al 75%
Acoustic pressure	63 dB(A) at 7 m
Length (mm)	1030
Width (mm)	620
Height (mm)	804
Dry weight (Kg)	183
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR

Engine manufacturer

Honda
