



TELWIN ENERGY 650 START 230-400V 12-24V

Reference: 829385

TELWIN ENERGY650 START CHARGER 230-400V 12-24V 2,5KW

Telwin Energy650 Start is a battery charger and starter with a power of 2,5KW for charging free electrolyte (WET) and lead acid (START&STOP) batteries with a voltage of 12/24V.

The **2,5KW battery charger** Telwin Energy650 allows the quick start of all types of cars, vans, light trucks, construction equipment and trucks.

The Telwin charger gives the possibility to select **3 modes: normal, quick (BOOST) and finally quick start**, according to the user's need.

Telwin Energy650 is equipped with fast charging timer. Equipped with protection systems both against overloads and for polarity reversals. Equipped with display for current charge. Equipped with remote control.

Telwin Energy650 is a 2,5KW battery charger with high performance and comfortable both in transport and use thanks to the handle and wheels that make it handy and easy to move. Ideal for both the demanding hobbyist and the professional, being a versatile, high performance and reliable product.

The Telwin Energy650 charger has a voltage of 12/24V and its maximum output current is 1000A and the charging power is 2,5KW. It has a maximum capacity of 1200Ah, its dimensions are 365x460x755mm while its weight is 38kg. Standard is equipped with two clamps, one mass and one positive and a remote control.

TECHNICAL CHARACTERISTICS OF THE BATTERY CHARGER 2,5KW TELWIN ENERGY650 START

Phase Type: Single Phase/Three-Phase
Three-Phase Mains Voltage: 230 V/ 400V
Frequency: 50 / 60 Hz
Charging Power: 2,5KW
Exit Power: 20 KW
Charging Voltage: 12 / 24 V
Effective Current: 100 A
Current EN60335-2-29: 80 A
Current Adv. 1v/c EN60335-2-29: 640 A
Maximum initial current: 1000 A
Min.ref. capacity: 20 Ah
Max. ref. capacity: 1200 / 800 Ah

Adjustment positions: 5
Length: 36.5 cm
Width: 46 cm
Height: 75.5 cm
Weight: 38 Kg

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range **TELWIN** and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer

Technical Sheet

Phase	Single phase / Three phase
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Power (W)	10000
Effective current (A)	90
Adjustment positions	5
Charging voltage (V)	12 / 24
Length (mm)	365
Width (mm)	460
Height (mm)	755
Dry weight (Kg)	38
Overload protectors	Yes
Video	2I3AIIWsa3c