



TRUMA COMBI D 6E Diesel + Electric Heater 6 KW for Camper and Truck

Reference: 010 C6DE-CPI /

TRUMA COMBI D6 AND 6 KW DIESEL/ELECTRIC HEATER FOR CAMPERS AND TRUCKS

TRUMA COMBI D 6E is a diesel and electric powered stove suitable for heating trucks and campers, capable of delivering a maximum heat output of 6KW.

The powerful Truma Combi D 6E heats up even the largest motorhomes in no time. The device also has an integrated 10-liter water tank that can be heated if necessary.

No additional boilers are needed, thus saving weight and space. The Truma Combi is also extremely compact and can therefore be installed in the vehicle with great flexibility.

Depending on the required power requirement, you can choose between diesel, electric or mixed power, thanks to this incredible versatility you can set your TRUMA COMBI D 6E according to the season or the desired temperature.

Technical characteristics TRUMA COMBI D 6E

Type of power supply Light oil compliant with EN 590
Nominal output for gas operation 2000 W / 4000 W / 6000 W
Nominal output for electrical operation 900 W / 1800 W
Nominal output for mixed operation max. 5800 W
Fuel consumption 220 - 630 ml / h (110 ml / h with average heat output equal to 1000 W)
Absorbed current (at 12 V): heating and water tank operation 1.8 - 4 A
Current consumption (at 12 V): water tank heating max. 1.8 A
Current consumption (at 230 V): 3.9 A / 7.8 A
Air flow (free exhaust) with 4 hot air outlets max: 287 m³ / h
Quiescent current: approx. 1 mA
Capacity: 10 liters
Max pump pressure: 2.8 bar
Max system pressure: 4.5 bar
Time warm up (approx. 15 °C to approx. 60 °C): Water tank approx. 20 Min / according to EN 15033 approx. 80 Min.
Net weight: 16.9 kg
Dimensions (L x W x H): 525 x 450 x 300 mm
Overall dimensions (L x W x H): 540 x 500 x 350 mm

Do you have a product with different characteristics? [HERE](#) you can find the full range of TRUMA or other specialized brands

The images and technical data and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Fuel	Diesel + Electric
Frequency (Hz)	50
Voltage (V)	230
Tank capacity (L)	10
Max rated heat power	6000 W
Min rated heat power	2000 W
Max Gas consumption (Kg/h)	0.46
Min Gas consumption (Kg/h)	0.16
Air flow (m ³ /h)	287
Length (mm)	525
Width (mm)	450
Height (mm)	300
Weight (Kg)	16.8