



PRAMAC LIFTER SCALE TRUCK PX25

Reference: G6B330UV100

The scale trucks range are equipped with a functional and precise weighing device with several operating options, suitable for lifting heavy loads.

Display

The PX20 pallet truck is a simple, economical and robust tool to be used for the weighing of transported loads. Its large-sized LCD display allows for easy reading of weight and the setting of tare simply and immediately.

Frame structure

The structure is made up of a double frame and a lower fork on which a counter fork is placed; both forks house four load cells that allow for a uniform load distribution, thus keeping weighing precision even in case of collision and unbalanced load.

The images are purely indicative.

Technical Sheet

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	2500
Load centre distance (mm)	600
Load axle to end forks (mm)	975
Wheel base (mm)	1250
Service weight (Kg)	113
Axle load, laden rear (Kg)	1830
Axle load, laden front (Kg)	783
Axle load, unladen front (Kg)	71
Axle load, unladen rear (Kg)	42
Tyres: front wheels	POLY.C

Tyres: rear wheels	POLY.I.
Diameter steering wheels (mm)	200
Width steering wheels (mm)	55
Diameter load rollers (mm)	82
Width load rollers (mm)	60
Quantity rear wheels	4
Quantity front wheels	2
Rear balancing axle	No
Tread front (mm)	155
Tread rear (mm)	375
Lift height (mm)	115
Height of tiller in drive position max (mm)	1160
Height of tiller in drive position min (mm)	690
Height lowered (mm)	90
Overall length (mm)	1596
Length to face of forks (mm)	411
Overall width (mm)	555
Thickness fork (mm)	60
Width fork (mm)	180
Length fork (mm)	1185
Distance between fork arms (mm)	555
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	1851
Turning radius (mm)	1426
Lifting speed laden (strokes)	13
Lifting speed unladen (strokes)	13
Lowering speed laden (m/s)	0.05
Lowering speed unladen (m/s)	0.02
Weigher	Yes