



MENNEKES EVERGUM SOCKET COMBINATION 70025

Reference: 70025

MENNEKES EVERGUM SOCKET COMBINATION 70025

MENNEKES EVERGUM 70025 is a combination of single-phase/three-phase receptacles, in one easy-to-use panel, with IP 44 rating.

Mennekes EVERGUM 70025 di is a versatile and reliable device designed to meet electrical connection needs in industrial and commercial environments. This unit combines several electrical outlets, fuses and protective devices within a rugged solid rubber enclosure.

The basic configuration of the unit includes a 63 A, 5 p and 400 V outlet, ideal for powering high-power equipment. There is also a 32 A, 5 p and 400 V outlet and a 16 A, 5 p and 400 V outlet, which allow devices of different power ratings to be connected. In addition, there are four 16 A, 230 V SCHUKO sockets for connecting commonly used devices.

Protection is provided by a pre-installed fuse, consisting of a 63 A, 4-pole, 0.03 A RCD residual current circuit breaker, which protects against ground faults, and a 32 A, 3-pole MCB circuit breaker and a 16 A, 3 p MCB, both of breaker class C. There are also two 16 A, 1-pole MCBs, of interruption class B, to protect individual circuits.

Mennekes EVERGUM 70025 is equipped with a 3-meter H07RN-F5G10 power cord with a 63 A, 5-pin, 400 V CEE plug, providing a reliable and secure connection. Protection from external agents is provided by IP44, which protects against the ingress of solids greater than 1 mm and water splashes.

Mennekes EVERGUM 70025 is made of solid rubber, which offers resistance to impact, chemicals and weathering, making it suitable for use in harsh environments. Mennekes EVERGUM 70025 complies with safety and quality regulations and is accompanied by an EAC declaration of conformity. It also has a storage compartment for convenient storage of accessories.

TECHNICAL CHARACTERISTICS MENNEKES EVERGUM 70025

NO.1 CEE 63 A, 5 P, 400 V

N.1 CEE 32 A, 5 P, 400 V

N.1 CEE 16 A, 5 P, 400 V

N.4 SCHUKO 16 A, 230 V

Protection: No.1 Int. differential 63A, 4P, 0.03A / No.1 Int. thermal-magnetic 32A, 3P, C / No.1 Int. thermal-magnetic 16A, 3P, C / No.2 Int. thermal-magnetic 16A, 1P, B

InA: 63 A

RDF: 0.6

Connection possibilities / Power cable: 3 m H07RN-F5G10 with CEE plug 63 A, 5P, 400 V

Degree of protection: IP 44

Material: rubber

Length: 360 mm

Width: 340 mm

Height: 330 mm
Weight: 15 kg

Looking for a product with different features? [HERE](#) you can find the full range of accessories for MENNEKES generator sets or other specialized brands.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Technical Sheet

Sockets configuration	1 x 400V 63A 5P CEE - 1 x 400V 32A 5P CEE - 1 x 400V 16A 5P CEE - 4 x 230V 16A SCHUKO
Protection degree	IP44
Material	Rubber
Length (mm)	360
Width (mm)	340
Height (mm)	330
Product type	Socket box
Fusing	1 x RCD 63A, 4P, 0.03A - 1 x MCB 32A, 3P, C - 1 x MCB 16A, 3P, C - 2 x MCB's 16A, 1P, B
Pre-fuse max. (A)	63
InA (A)	63
RDF	0.6
Connection / Feeder cable	3 m H07RN-F5G10 with CEE-plug 63 A, 5P, 400 V
Weight (Kg)	15