



CGM SUPERPOWER 6000SPE GENERATOR SINGLEPHASE 6KVA

Reference: CGM 6000 SPE

CGM SUPERPOWER 6000SPE GENERATOR SINGLEPHASE 6KVA 4.8KW AVR

The **Generator Singlephase 6KVA CGM SUPERPOWER 6000SPE AVR** are powered by **gasoline**, are equipped with electric and manual start, handles and wheels to carry it easily; like the whole range CGM SUPERPOWER 6000SPE, is a generator singlephase 6KVA that respects a high quality standard and guarantees a high level of reliability. The whole range of generator singlephase 6KVA has passed different tests for each component of which the groups and the final product are composed.

The strengths of the generator singlephase 6KVA are: the high quality of the components, the lightness, the compactness, the ease of use and also the modern design, equipped with a practical rope starter.

The CGM Superpower 6000SPE è specially developed for camping, caravans, houses, and hobby applications, etc. è able to power a wide range of appliances.

CGM Superpower 6000SPE is equipped with a convenient **counter**, **larger tank rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the generator singlephase 6KVA CGM Superpower 6000SPE to deliver stable energy and can therefore connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the unit is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with safe and stabilized energy.

Technical features of the generator singlephase 6KVA CGM SUPERPOWER 6000SPE

Maximum Power Single-phase: 4.8 KW

Maximum Power Single-phase: 6 KVA

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Motor: CGM 14. 0HP

Starting: Manual / Electrical

Consumption: 1.8 Lt/h

Length: 717 mm

Width: 545 mm

Height: 592 mm

Weight: 69 Kg
 AVR

Discover the whole range of [industrial and portable current generators](#)

Images and technical data not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4.8
Maximum power single phase (KVA)	6
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V
Engine	CGM 14.0HP, 4 stroke
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Starting system	Manual / Electric
Engine capacity (cm ³)	420
Number cylinders	1
Alternator	Copper
Fuel tank capacity (L)	25
Consumption (L/h)	1.8
Running time (h)	13.89
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	717
Width (mm)	545
Height (mm)	592
Dry weight (Kg)	69
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	CGM