



GENSET MG 66 S-I - SINGLE-PHASE/THREE-PHASE GENERATOR 66 KVA AVR

Reference: MG 66 S-I

GENSET MG 66 S-I

The GENSET MG 66 S-I is a 66 KVA single/three phase diesel generator set with electric start and AVR voltage regulator. The GENSET MG 66 S-I also has a low fuel consumption: only 10.2 Lt/h at 75% of the load. Thanks to the high quality and efficiency of its components, the GENSET MG 66 S-I generator set is ideal for various types of professional work such as on large construction sites.

Images and technical data are not binding.

Technical Sheet

| Phase | Single phase / Three phase |
|------------------------------------|-----------------------------|
| Maximum power single phase (KW) | 17.6 |
| Maximum power single phase (KVA) | 22 |
| Maximum power three phase (KW) | 60 |
| Continuous power three phase (KW) | 48 |
| Maximum power three phase (KVA) | 66 |
| Continuous power three phase (KVA) | 52.8 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Sockets configuration | Terminal box |
| Engine | FPT (IVECO) NEF45SM1A turbo |
| Emissions Regulations | Stationary Use |
| Engine rpm (rpm) | 1500 |
| Starting system | Electric |
| Engine capacity (cm ³) | 4500 |
| Number cylinders | 4 |

| | |
|------------------------|-----------------|
| Cooling | Water |
| Alternator | Synchronous |
| Protection degree | IP23 |
| Motor insulation class | H |
| Fuel tank capacity (L) | 230 |
| Consumption (L/h) | 8.1 |
| Running time (h) | 22.5 |
| Acoustic power | 95 dB(A) |
| Acoustic pressure | 70 dB(A) at 7 m |
| Length (mm) | 2900 |
| Width (mm) | 1100 |
| Height (mm) | 1800 |
| Dry weight (Kg) | 1400 |
| Silenced | Yes |
| Super silenced | Yes |
| Product type | Generator |
| ATS Switch device | ATS Included |
| Voltage regulator | AVR |
| Engine manufacturer | FPT Iveco |