

## GENMAC QUEEN G60JS-E3 THREE-PHASE 54 KVA DIESEL - MOTOR JOHN-DEERE STAGE 3A



Reference: QUEEN G60JS-E3- MOTORE JOHN-DEERE STAGE 3A-AVR

### GENMAC QUEEN G60JS-E3

The GENMAC QUEEN G60JS-E3 is a 54 KVA super-silenced single-phase/three-phase diesel generator with Stamford alternator and AVR voltage regulator.

Thanks to its diesel fuel supply, the GENMAC QUEEN G60JS-E3 can only consume 0.15 m<sup>3</sup>/h at full load and has a low environmental impact, making it one of the best in its class.

The long life and reliability of the GENMAC QUEEN G60JS-E3 is due to a special control procedure during the various stages of production.

The GENMAC QUEEN G60JS-E3 is suitable for applications in different contexts such as: hospitals, industries, shopping malls, hotels, airports, banks, universities, stadiums, offices, etc.

The Stage 3A engine allows the use of the generator set also for mobile use, for example for roadworks and rental services.

### Control panel features

#### QT2A-4520

Self-standing tower with IP65 metal box  
Circuit breaker  
AMF controller DSE4520- Voltmeter, Frequency meter, Ammeter-  
Generator power (kW, kV Ar, kV A & pf) monitoring- Hour meter- Fuel level meter- Overload (kW & kV Ar) protection- Low oil pressure protection- High coolant temperature protection- Low fuel level protection- Battery charger alternator fault- Rpm protection  
Emergency stop button  
Audible alarm  
Terminal board for ATS connection  
Can Bus reading Port (if standard on the engine)  
Battery charger  
On/off switch

Images and technical data are not binding.

### Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	48
Continuous power three phase (KW)	43
Maximum power three phase (KVA)	60
Continuous power three phase (KVA)	54
Fuel	Diesel
Frequency (Hz)	50

Voltage (V)	230 / 400
Emissions Regulations	Stage 3A
Engine rpm (rpm)	1500
Speed governor	Mechanical
Engine capacity (cm <sup>3</sup> )	4500
Number cylinders	4
Oil capacity (L)	12
Cooling	Water
Alternator	Synchronous, self-excited
Width (mm)	1056
Height (mm)	1900
Dry weight (Kg)	1450
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	John Deere