

VILLAGE MARINE WATERMAKER LTM-1800

Reference: 90-6056



Village Marine Watermaker LTM-1800

Village Marine LTM-1800 single phase desalinator with 220 V power supply and 60 Hz frequency. The Village Marine LTM-1800 desalinator has a capacity of 205 litres/hour.

The LTM-1800 Village Marine Desalinator offer high quality Parker Village Marine engineered components with simple manual operation. Driven by AC motors, the modular configuration is ready to mount modules for flexible installation options. Integrated into each LTM unit is a control manifold, which includes a regulator and a bypass valve.

Some specifications of the LTM-1800 Desalinator

- Powder coated mounting brackets included
- 5 micron of cleanable prefilter
- The control manifold pressure regulator ensures constant pressure and prevents over- or under-pressurization of the unit. Adjustable to allow operation in brackish or fresh water
- High-quality spiral wound TFC reverse osmosis membranes with spiral wound
- Magnetic drive thrust pump
- Stainless steel pressure gauges filled with glycerine
- High pressure piston pump with 316 stainless steel head
- Acrylic flowmeter for production monitoring

Technical characteristics:

Phase type: Single-phase
Power supply: 220 VDC
Frequency: 60 Hz
Flow rate: 284 Lt/h
Weight: 76 Kg

If you are looking for another desalinator similar to the Village Marine LTM-1800 then you can browse our entire catalogue dedicated to [marine desalinators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	60

Feed Type	220 V
Capacity (Lt/h)	284
Weight (Kg)	76
