

Desalinator Idromar MC1J



Reference: MC1J

Desalinator Idromar MC1J

Desalinator Idromar MC1J belonging to the MINI COMPACT series is an excellent desalinator with an hourly production of fresh water at 25°C equal to 65 litres/hour and a daily production at 25°C equal to 1500 litres/day.

The Idromar MC1J desalinator is designed with high quality components with a simple operation.

With a fresh water production ranging from 65 to 180 lt/h, the desalinators of the MINI COMPACT series are the Idromar proposal for medium-small boats (from 15 to 25 meters), where an intensive and continuous use is not always necessary. The desalinators of this range are compact, in decomposable version and share the same functionality, practicality and homogeneity of materials. One of the main features that the Idromar MC1J desalinator has in common with those of its range is the use of 316L stainless steel: from the small details such as bolts and nuts, the entire frame, the vessels containing the membranes and the high pressure pump head made of stainless steel to eliminate the phenomenon of corrosion.

The Idromar MC1J desalinator provides a practical and reliable source of fresh water for yachtsmen with high supply requirements. The Idromar MC1J desalinator offers you absolute water independence for various leisure activities such as long trips, ocean crossings or fishing.

Technical features of the Idromar MC1J desalinator:

Hourly production at 25°C: 65 Lt/h

Daily production at 25°C: 1500 Lt/h

Salinity of water produced: 300/400 PPM

Power consumption: 1.5 KW

Length: 790 mm

Width: 450 mm

Height: 380 mm

Weight: 75 Kg

Hydraulic connexion

Sea suction: 1/2"

Suction boxes: 1/2"

Discharge: 3/8"

Production: 3/8"

If you are looking for another desalinator similar to the Idromar MC1J then we suggest you browse our entire catalogue dedicated to [marine desalinators](#).

Images and technical data are not binding.

...

Technical Sheet

Power (W)	1500
Length (mm)	790
Width (mm)	450
Height (mm)	380
Feed Type	230 V
Production for hour at 25°C (Lt/h)	65
Daily production at 25°C (Lt/day)	1500
Salinity of water produced (PPM)	300/400
Capacity (Lt/h)	65
Remote panel	Digital
Weight (Kg)	75