

IDROMAR WATERMAKER MSK6



Reference: MSK6

IDROMAR WATERMAKER MSK6

The Watermaker Idromar MSK6 part of the MINI COMPACT series is an excellent Watermaker with an hourly production of fresh water at 25°C of 65 liters/hour and a daily production at 25°C of 1500 liters/day.

The Watermaker Idromar MSK6 is designed with high quality components with a simple operation. With a fresh water production that varies from 65 to 180 lt/h, the Watermaker of the MINI COMPACT series are the Idromar proposal for medium-small boats (from 15 to 25 meters), where an intensive and continuous use is not always necessary. The Watermaker of this range are compact, in decomposable version and share the same functionality, practicality and homogeneity of the materials.

One of the main features that the Idromar MSK6 Watermaker has in common with those in its range is the use of 316L stainless steel: from small details such as screws, bolts and nuts, the entire frame, the vessels that contain the membranes and the high pressure pump head are made of stainless steel to eliminate the phenomenon of corrosion.

The Idromar MSK6 Watermaker provides a practical and reliable source of fresh water for boaters with high supply requirements. The Idromar MSK6 Watermaker offers you absolute water independence for various diversions such as extended voyages, ocean crossings or fishing. The Idromar MSK16 Watermaker systems are small and efficient able to fit into the tightest of spaces due to their complete decomposability.

Technical characteristics of the Watermaker Idromar MSK6:

Hourly production at 25°C: 65 Lt/h
Daily production at 25°C: 1500 Lt/h
Produced water salinity: 300/400 PPM
Absorbed power: 1.5 KW
Length: 500 mm
Width: 340 mm
Height: 480 mm
Weight: 75 Kg

Hydraulic connections

Sea suction: 1/2"
Caskets suction: 1/2"
Exhaust: 3/8"
Outflow: 3/8"

If you are looking for another Watermaker similar to the Idromar MSK6 then we recommend that you browse our entire catalog dedicated to [nautical watermakers](#).

Images and technical data are not binding.

Aliquam erat volutpat. Integer venenatis nunc mauris. Integer sit amet dolor consequat, viverra urna vitae, placerat diam. Nullam ex turpis, tempor gravida nulla vitae, consequat aliquam risus. Sed faucibus blandit sodales. Ut blandit, nibh in egestas pulvinar, justo tellus mollis nibh, sed lacinia orci lorem non lacus. Mauris auctor justo quis ultricies laoreet. Vivamus vitae nisi magna. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos himenaeos. Ut rutrum risus sed nisi fringilla ullamcorper. Nullam non leo in.

""

Technical Sheet

Power (W)	1500
Length (mm)	500
Width (mm)	340
Height (mm)	480
Feed Type	230 V
Production for hour at 25°C (Lt/h)	65
Daily production at 25°C (Lt/day)	1500
Salinity of water produced (PPM)	300/400
Capacity (Lt/h)	65
Remote panel	Digital
Weight (Kg)	75