



CGM D4000T THREE-PHASE GENERATOR 4KVA

Reference: CGM D4000T

CGM D4000T three-phase generator 4KVA

CGM D4000T three-phase generator 4KVA with a Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, mounted on a fixed base with vibration dampers.

The CGM D4000T generator set is composed of a Made in Italy alternator by Linz or NSM, self-excited with brushes and with AVR voltage regulator. The CGM D4000T generator set is equipped with electric start with 12 V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load.

This CGM D4000T is perfect for outdoor use such as hobby use.

The CGM D4000T generator set is part of the CLASSIC DIESEL series and are characterized by lower consumption and a longer life expectancy than the gasoline powered range. The CGM D4000T at 3000 rpm is suitable for emergency use only. It is not recommended for use for more than 6 hours continuously and for more than 500 hours per year.

Technical characteristics of CGM D4000T:

Type of phase: Singlephase / Threephase
Maximum singlephase power: 1.5 KVA / 1.2 KW
Continuous singlephase power: 1.3 KVA / 1 KW
Maximum threephase power: 4.4 KVA / 3.5 KW
Continuous threephase power: 4 KVA / 3.2 KW
Fuel: Diesel
Voltage: 230/400 V
Frequency: 50 Hz
Motor: KOHLER KD15-350
Engine rpm: 3000 rpm
Starting: Electric
Voltage regulator system: AVR
Consumption: 1 Lt / h at 75% of the load
Capacity tank: 4.3 Lt
Autonomy: 4.3 h at 75% of the load
Length: 780 mm
Width: 510 mm
Height: 500 mm
Weight: 80 Kg

Discover the full range reserved for [generators](#) of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	1.2
Continuous power single phase (KW)	1
Maximum power single phase (KVA)	1.5
Continuous power single phase (KVA)	1.3
Maximum power three phase (KW)	3.5
Continuous power three phase (KW)	3.2
Maximum power three phase (KVA)	4.4
Continuous power three phase (KVA)	4
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE
Engine	Kohler KD 15-350
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	349
Number cylinders	1
Alternator	Made in Italy
Poles	2
Fuel tank capacity (L)	4.3
Consumption (L/h)	1
Running time (h)	4.3
Length (mm)	780
Width (mm)	510
Height (mm)	500
Dry weight (Kg)	80
Silenced	No

Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kohler
