



## CLIMMA COMPACT 10 RC

Reference: MCN10K3BRCU

### Conditioner CLIMMA Compact 10RC Reverse cycle (heat pump)

Independent air conditioner Climma Compact 10RC perfect to condition a single room or contiguous environments.

The Climma Compact 10RC air conditioner is specially designed for marine applications, just as all air conditioners in the Climma Compact range are water cooled. Compact, quiet and powerful, the Climma Compact 10RC air conditioner works with environmentally friendly refrigerant and comes with the option of cycle reversal to heat the environment.

The Climma Compact 10RC air conditioner is also available in cold only or electrically heated version.

This version of the Climma Compact 10RC air conditioner is reverse cycle (heat pump).

For multiple installations with two or more air conditioners, a replay box is also available to use a single sea water pump.

#### Technical characteristics of the Climma Compact 10RC air conditioner:

Phase type: Single-phase

Voltage: 115 / 230 V

Frequency: 50 / 60 Hz

Cold capacity: 10000 BTU/h

Heat capacity: 10000 BTU/h

Duct size: 125 mm

Maximum air flow: 530 m<sup>3</sup>/h

Length: 523 mm

Width: 330 mm

Height: 340 mm

Weight: 35 Kg

#### Main advantages:

- Independent air conditioning systems from 3500 to 27000 BTU/h
- Ecological refrigerant R410A for maximum efficiency and minimal consumption
- High efficiency ultra-fine gas-air cooler
- Powered and movable fan
- Pre-wired electrical box
- Threaded brass condensate drain and anti-condensation tray with Climma Dry Pan system
- High efficiency condenser

#### R410a

Ecological refrigerant that does not contain toxic chemicals that damage the ozone layer.

More efficient cooling system due to better heat exchange and less pressure drop.

If you are looking for another air conditioner like the Climma Compact 10RC then you can browse our catalogue reserved for marine air conditioners.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60
Voltage (V)	115 / 230
Maximum flow (m <sup>3</sup> /h)	530
Refrigerating yield	10000 BTU/h
Heating power	10000 BTU/h
Length (mm)	523
Width (mm)	330
Height (mm)	340
Product type	Air conditioner
Coolant	R410A
Weight (Kg)	35