

WEBASTO COOL TOP TRAIL 20



Reference: HGN47480031

WEBASTO Cool Top Trail 20 air conditioner

The WEBASTO Cool Top Trail 20 air conditioner is a 230V single-phase roof air conditioner with 2000W cooling power and 2000W heating power and is suitable for use in parked campers and trailers up to 8 meters in length. The WEBASTO Cool Top Trail 20 is lightweight, compact and easy to install in small vehicles such as trucks, campers, caravans or trailers.

Thanks to its generous heat exchanger, the WEBASTO Cool Top Trail 20 air conditioner is characterized by high efficiency and high performance. The reliability and high cooling performance of the WEBASTO Cool Top Trail 20 have been tested under extreme conditions at temperatures of up to 50 °C. Units like this roof air conditioner are equipped with a heat pump as standard which is also very powerful and can operate at outside temperatures down to -5 °C.

The very low noise levels of the WEBASTO roof air conditioner allow you to rest and relax inside the vehicle and not disturb the neighbours at the campsite. The use of high-quality components ensures robustness and a long life with minimal maintenance costs. Made of UV-stabilised polypropylene, the air conditioner housing is robust yet lightweight.

The air conditioners can be operated with an easy-to-use remote control which allows the user to access all the functions of the air conditioner conveniently from the dining area, seat or bed.

In addition to cooling and heating, the air conditioners include several extra functions such as dehumidification, timer and sleep function. The WEBASTO Cool Top Trail is supplied with a mounting frame for roof openings of 400 x 400 mm.

For use in smaller openings of 360 x 360 mm, an alternative adapter frame is available as an accessory.

Technical specifications of the CoolTopTrail 20 roof air conditioner:

Cooling capacity: 2000 W
Heating capacity: 2000 W
Voltage: 230 V
Frequency: 50 Hz
Rated current (cooling mode): 3 A
Rated current (heating mode): 2.6 A
Operating temperature range (°C): -5 to 50
Roof thickness (mm): 25 to 85
Roof opening dimensions (mm): 400 x 400 (360 x 360 with optional adapter)
Dimensions of the external unit: 1002 x 566 x 215 mm
Dimensions of the internal unit: 557 x 536 x 43 mm
Total weight: 30,8 Kg
environmentally friendly refrigerant gas: R32

The advantages of this roof air conditioner:

- Powerful air conditioners with high cooling and heating capacity
- Robust, lightweight and quiet
- Wide operating range from -5 to 50 °C

- Slim profile and compact design
- Easy installation

Equipment:

- Outdoor unit
- Indoor unit
- Frame adapter 400x400 mm
- Remote control
- Installation manual

If you are looking for another type of product such as the WEBASTO Cool Top Trail 20 roof air conditioner, you can browse our entire catalog of [vehicle air conditioners](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Refrigerating yield	2000 W
Heating power	2000 W
Roof thickness (mm)	25 to 85
Roof notch (mm)	400x400
Length (mm)	1002
Width (mm)	566
Height (mm)	215
Type of climate control	Roof Air Conditioner
Recommended vehicle length (m)	8
Product type	Air conditioner
Coolant	R32
Weight (Kg)	30.8
Operating temperature range (°C)	-5 to 50