



WEBASTO AC LIVE TYP-2 4.5 11KW ELECTRIC CAR CHARGING STATION

Reference: 5110360C

WEBASTO AC LIVE TYP-2 4.5 ELECTRIC CAR CHARGING STATION 11KW

WEBASTO AC LIVE is a charging station for electric cars capable of delivering a maximum charging power of 11 KW with a programmable digital interface.

With the Webasto Live intelligent electric car station you can reap the benefits of electromobility in an efficient and optimized way to meet your needs both for your business and at home.

WEBASTO AC LIVE is equipped with an integrated 4G modem and configurable digital interface via Wi-Fi hotspot, allowing you to always have the station under control and monitor, manage and control activities at any time digitally.

Thanks to regular online updates, your electric car station remains future-proof and meets the highest quality standards in every respect.

The WEBASTO electric car station boasts high charging power, maximum safety and maximum convenience. Charging with electric car station WEBASTO is up to 10 times faster than a typical household outlet and automatically stops as soon as the battery is charged.

Technical Specifications WEBASTO AC LIVE:

Nominal current (A): 16, 32
Phase type: Three-phase / Single-phase
Main voltage: 230/400 V (European)
Main frequency: 50 Hz
Overvoltage category: III according to EN 60664
Protection class: I
Cable length: 4.5 m
Protection device: IP54
Mechanical impact protection: IK08
Output voltage: 230 / 400 Vac
Max power: 11 KW
Display: 8 RGB LEDs,, buzzer
Width: 225 mm
Depth: 116 mm
Height: 447 mm
Weight: 4.4 Kg

The WEBASTO station impresses with its many advantages:

- Charging capacity of 11 kW, 4.5 m
- Up to ten times faster than using a standard household outlet

- Simple and convenient operation
- Safe operation including protective measures
- High quality engineering
- Affordable price and expert technical support
- High quality "Made in Germany"

If you are looking for a Webasto charging station or other similar products then you can browse our entire [catalogue](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	11
Maximum power three phase (KW)	
Frequency (Hz)	50
Voltage (V)	230 / 400
Protection degree	IP54
Nominal current (A)	16 or 32
Length (mm)	116
Width (mm)	225
Height (mm)	447
Product type	Charging station
Weight (Kg)	4.4
Overvoltage category	III in accordance with EN 60664
Network systems	TT/TN/IT
EMC class	Interference emission: Class B (residential, commercial, industrial areas) Interference resistance: industrial areas
Assembly	Wall or stand mounting
Power cable	Mounted on-wall or in-wall
Cross section of the connection (cable dimensions)	Cross-section of the connection cable (Cu) depending on local conditions: 6 or 10 mm ² for 16 A and 10 mm ² for 32 A
Charging cable	Type 2 in accordance with EN 62196-1 and EN 62196-2 up to 32 A / 400 V AC; 4.5 m long, integrated cable bracket
Output voltage (VAC)	230 / 400
Max. charging capacity (KW)	3.7 - 22 (adjustable)
Display	8 RGB-LEDs, horn beeper
Network interfaces	- LAN (RJ45) - 10 / 100 Base-TX - WLAN 802.11b/g - 54 Mbit/s
Mobile communications	SIM card slot (form factor 3FF / Micro-SIM), integrated 4G modem (LTE)
OCCP	Version 1.5 / 1.6 (upgrade possible)

Plug & Charge	ISO 15118-1, ISO 15118-2
Local recharge management	Up to 250 charging points, dynamic, no phase delay adjustment
Solar charging / optimized speed	Programmed
Protection against mechanical impact	IK08
Operating temperature range (°C)	From -25 to +40
Storage temperature range (°C)	from -25 to +70
Permissible relative humidity (%)	From 5 to 95 without condensation
Altitude (m)	Max 2000 m above sea level