

HELVI DISCOVERY 250

Reference: 99000082



HELVI DISCOVERY250 Battery charger

HELVI DISCOVERY250 is part of the new range of fully electronic battery chargers without output voltage peaks that can damage the electronic boards on board vehicles. HELVI DISCOVERY250 is ideal to charge AGM, GEL and lead batteries and is equipped with 12/24 V voltage selection, charging current on nine levels, ideal for cars, vans, small boats. HELVI DISCOVERY250 also has desulphation function and liquid crystal display with 12 V or 24 V battery voltage selection. HELVI DISCOVERY250 is also ideal for Lithium batteries (LiFePO₄).

HELVI DISCOVERY250 is perfect for charging batteries with a 12 V or 24 V voltage and a charging current of 16 A (12 V) or 8 A (24 V). The HELVI DISCOVERY250 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI DISCOVERY250 battery charger are in the automotive, domestic, custom and agricultural sectors.

HELVI DISCOVERY250 is an intelligent management battery charger with high efficiency, low loss, light weight, and good looks.

HELVI DISCOVERY250 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. HELVI DISCOVERY250 has a rated power of 230 W.

The nominal charging capacity of the HELVI DISCOVERY250 battery charger is 250 Ah and has 9 charging positions.

HELVI DISCOVERY250 is very compact and extremely light thanks to its weight of about 1 Kg.

Technical characteristics of the HELVI DISCOVERY250 battery charger:

Phase type: Single-phase

Voltage: 230 V

Frequency: 50/60 Hz

Power: 300 W

Battery voltage: 12/24 V

Charging current: 16 A (12 V) - 8 A (24 V)

Charging capacity: 250 Ah 15h

Charging positions: 9

Length: 295 mm

Width: 125 mm

Height: 75 mm

Weight: 1.2 Kg

If you are looking for another product similar to the HELVI DISCOVERY250 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Technical Sheet

Phase

Single phase

Frequency (Hz)	50 / 60
Voltage (V)	230
Power (W)	300
Adjustment positions	9
Nominal current (A)	16 A (12 V) - 8 A (24 V)
Charge capacity (Ah)	250
Battery voltage (V)	12 / 24
Charging voltage (V)	12 / 24
Length (mm)	295
Width (mm)	125
Height (mm)	75
Product type	Battery Charger
Weight (Kg)	1.2