



HELVI RAPID 280

Reference: 99005040

HELVI RAPID280 Battery charger

HELVI RAPID280 is a battery charger with starter, portable with charge current selector, ammeter, thermostatic protection against long starts, internal fuse against short circuits and polarity reversal.

The HELVI RAPID280 battery charger is perfect for charging batteries with 12 V voltage and 25 A current.

The HELVI RAPID280 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors.

The main applications of the HELVI RAPID280 battery charger are in the automotive, domestic and agricultural sectors.

HELVI RAPID280 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. The HELVI RAPID280 battery charger has a rated power of 460 W for a maximum current of 38 A.

The nominal charging capacity of the HELVI RAPID280 battery charger is 375 Ah and has 2 charging positions (min-max) plus Boost.

HELVI RAPID280 is very compact and very light thanks to its weight of about 12 Kg.

Technical characteristics of the HELVI RAPID280 battery charger:

Phase type: Single-phase

Voltage: 230 V

Frequency: 50/60 Hz

Power: 460 W

Battery voltage: 12 V

Maximum current: 38 A

Charging current: 25 A

Maximum surge current: 240 Acc

Charging capacity: 375 Ah 15h

Charging positions: 2 + Boost

Length: 235 mm

Width: 220 mm

Height: 335 mm

Weight: 12.9 Kg

If you are looking for another product similar to the HELVI RAPID280 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60

Voltage (V)	230
Power (W)	460
Adjustment positions	2 + Boost
Nominal current (A)	25
Charge capacity (Ah)	375
Battery voltage (V)	12
Charging voltage (V)	12
Current max (A)	38
Length (mm)	235
Width (mm)	220
Height (mm)	335
Product type	Battery Charger
Weight (Kg)	12.9