



## HELVI AUTOSTAR 300

Reference: 99005043

### HELVI AUTOSTAR300 Battery charger

HELVI AUTOSTAR300 is a battery charger with portable starter equipped with selector and ammeter to adjust and display the charge current level. HELVI AUTOSTAR300 is protected with internal fuse against short circuits or polarity reversal and thermostatic protection against prolonged starts. HELVI AUTOSTAR300 is equipped with C.P.S. (car protection system) able to activate and deactivate the start function (boost) totally automatically, to protect the electronics on board the vehicle.

The HELVI AUTOSTAR300 battery charger is perfect for charging batteries with a 12 V voltage and a 25 A current.

The HELVI AUTOSTAR300 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI AUTOSTAR300 battery charger are in the automotive, domestic and agricultural sectors.

HELVI AUTOSTAR300 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. The HELVI AUTOSTAR300 battery charger has a rated power of 460 W for a maximum current of 38 A.

The nominal charging capacity of the HELVI AUTOSTAR300 charger is 375 Ah and has 2 charging positions (min-max) plus Boost.

HELVI AUTOSTAR300 is very compact and also light thanks to its weight of about 13 Kg.

#### Technical characteristics of the HELVI AUTOSTAR300 battery charger:

Phase type: Single-phase

Voltage: 230 V

Frequency: 50/60 Hz

Power: 460 W

Battery voltage: 12 V

Maximum current: 38 A

Charging current: 25 A

Maximum surge current: 300 Acc

Charging capacity: 375 Ah 15h

Charging positions: 2 + Boost

Length: 345 mm

Width: 250 mm

Height: 280 mm

Weight: 13.7 Kg

If you are looking for another product similar to the HELVI AUTOSTAR300 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

### Technical Sheet

Phase

Single phase

Frequency (Hz)	50 / 60
Voltage (V)	230
Power (W)	460
Adjustment positions	2 + Boost
Nominal current (A)	25
Charge capacity (Ah)	375
Battery voltage (V)	12
Charging voltage (V)	12
Current max (A)	38
Length (mm)	345
Width (mm)	250
Height (mm)	280
Product type	Battery Charger
Weight (Kg)	13.7