



HELVI AUTOSTAR 2000

Reference: 99010043

HELVI AUTOSTAR2000 Battery charger

HELVI AUTOSTAR2000 is a battery charger with portable starter equipped with selector and ammeter to adjust and display the charge current level. HELVI AUTOSTAR2000 is protected with internal fuse against short circuits or polarity reversal and thermostatic protection against prolonged starts. HELVI AUTOSTAR2000 is equipped with C.P.S. (car protection system) able to activate and deactivate the start function (boost) totally automatically, to protect the electronics on board the vehicle.

The HELVI AUTOSTAR2000 battery charger is perfect for charging batteries with a 12 V or 24 V voltage and a 120 A current.

The HELVI AUTOSTAR2000 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI AUTOSTAR2000 battery charger are in the automotive, construction and agricultural sectors.

HELVI AUTOSTAR2000 is a single-phase/three-phase battery charger with 230/400 V power supply and 50/60 Hz frequency. The HELVI AUTOSTAR2000 battery charger has a nominal power of 3600 W for a maximum current of 150 A.

The nominal charging capacity of the HELVI AUTOSTAR2000 battery charger is 1800 Ah and has 12 charging positions plus Boost.

HELVI AUTOSTAR2000 is very compact and comfortable to carry thanks to its wheels despite its weight of about 87 Kg.

Technical characteristics of the HELVI AUTOSTAR2000 battery charger:

Phase Type: Single/Triphase

Voltage: 230/400 V

Frequency: 50/60 Hz

Power: 3600 W

Battery voltage: 12/24 V

Maximum current: 150 A

Charging current: 120 A

Maximum surge current: 2000 Acc

Charging capacity: 1800 Ah 15h

Charging positions: 12 + Boost

Length: 330 mm

Width: 575 mm

Height: 770 mm

Weight: 87.8 Kg

If you are looking for another product similar to the HELVI AUTOSTAR2000 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Technical Sheet

Phase

Single phase / Three phase

Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Power (W)	3600
Adjustment positions	12 + Boost
Nominal current (A)	120
Charge capacity (Ah)	1800
Battery voltage (V)	12 / 24
Charging voltage (V)	12 / 24
Current max (A)	150
Length (mm)	330
Width (mm)	575
Height (mm)	770
Product type	Battery Charger
Weight (Kg)	87.8