



GENMAC CLICK RG4000HO GENERATOR 3,4KVA

Reference:

GENMAC CLICK RG4000HO GENERATOR 3,4KVA

The generator Genmac Click RG4000HO single phase has a Honda gasoline powered engine capable of delivering a power of 3,4KVA with the possibility of connection to optional AVR.

The Genmac Click RG4000HO single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 3.1 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The generator is very light and makes it very easy to move for other uses, in addition for an even easier and more dynamic portability is possible the optional supply of a practical transport kit dedicated to this line of generators.

The Genmac 3,4KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 3,4KVA Genmac Click RG4000HO

Power supply: Gasoline
Single-phase
Continuous output: 2.6KW
Continuous output: 2.9KVA
Maximum output: 3.1KW
Maximum output: 3,4KVA
Voltage: 230V
Frequency: 50 Hz
3000 revolutions per minute
Tank: 3.1 Lt.
Autonomy @ 75%: 2,6 h fixed revolutions
Starting: Manual
Length (mm): 620
Width (mm): 430
Height (mm): 430
Dry weight (Kg): 41

If you are looking for another product then you can consult on our catalog other [terrestrial gene-groups](#).

Images and technical data are not binding and may be subject to review

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.1
Continuous power single phase (KW)	2.6
Maximum power single phase (KVA)	3.4
Continuous power single phase (KVA)	2.9
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	4 Tempi
Engine rpm (rpm)	3000
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	4
Running time (h)	2.6
Length (mm)	620
Width (mm)	430
Height (mm)	
Dry weight (Kg)	41
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR (optional)