



GENMAC Combi RG4000HO-M5 GENERATOR 3,4KVA

Reference:

GENMAC Combi RG4000HO-M5 GENERATOR 3,4KVA

The generator Genmac Combi RG4000HO-M5 single phase has a GP200 4 strokes Stage V gasoline powered engine capable of delivering a power of 3,4KVA with the possibility of connection to optional AVR.

The Genmac RG4000HO-M5 single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 16 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The Genmac 3,4KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

The series of Combi generators has been designed according to the standards, for mobile use, with the possibility to have on customer's specific request the handling kit designed exclusively for the selected product.

Technical features of generator 3,4KVA Genmac Combi RG4000HO-M5

Power supply: Gasoline
Phase type: Single phase
Continuous power: 2.9KVA / 2.6KW
Maximum power: 3,4KVA / 3,1KW
Voltage: 230V
Frequency: 50 Hz
Engine: GP200 4 strokes
Emission regulation: Stage V
3000 rpm
Tank: 16 Lt.
Autonomy @ 75%: 13 h fixed rpm
Starting: Manual
Length (mm): 620
Width (mm): 430
Height (mm): 430
Dry weight (Kg): 52

If you are looking for another product then you can consult on [our catalog](#) other generator

Images and technical data are not binding and may be subject to review

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.1
Continuous power single phase (KW)	2.6
Maximum power single phase (KVA)	3.4
Continuous power single phase (KVA)	2.9
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	4 Tempi
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	16
Running time (h)	13
Length (mm)	620
Width (mm)	430
Height (mm)	
Dry weight (Kg)	52
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR (optional)