

GENMAC Click G7900HO GENERATOR 8KVA



Reference:

GENMAC Click G7900HO GENERATOR 8KVA

The **generator Genmac Click G7900HO** three phase has a Honda gasoline powered engine capable of delivering a power of 8KVA with the possibility of connection to optional AVR.

The GENMAC Click G7900HO generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 6,1 liters for an autonomy of about three and a half hours, complete with manual starter.

The Genmac 8KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 8KVA generator is equipped with capacitor voltage regulator, on request it is possible to supply it with AVR voltage regulator.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 5,8KVA Genmac Click G7900HO

Power supply: Gasoline
Starting: manual recoil
Phase type: Singlephase / Threephase
Singlephase continuous Output: 2.45 KVA / 2.2 KW
Maximum singlephase Output: 2.6 KVA / 2.4 KW
Threephase continuous Output: 7,3KVA / 5,8KW
Maximum threephase Output: 8KVA / 6,8KW
Socket panel: 1 x Schuko 230 V - 1 x 16 A 400 V
Voltage: 230 / 400V
Frequency: 50 Hz
3000 rpm
Tank: 6,1 Lt.
Life @ 75%: 2,9 h fixed

Emission regulations: STAGE V
Length (mm): 780
Width (mm): 540
Height (mm): 560
Dry weight (Kg): 80

If you are looking for another product then you can consult on [our catalog](#) other [terrestrial generator](#).

Images and technical data are not binding and may be subject to review

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	2.4
Continuous power single phase (KW)	
Maximum power single phase (KVA)	2.6
Continuous power single phase (KVA)	
Maximum power three phase (KW)	6.8
Continuous power three phase (KW)	5.8
Maximum power three phase (KVA)	8
Continuous power three phase (KVA)	7.3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Honda GX390
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	6.1
Running time (h)	2.9
Length (mm)	780
Width (mm)	540
Height (mm)	560
Dry weight (Kg)	80
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR (optional)