



## GENMAC Daily-GAS RG4700HS NG GENERATOR 5,3KVA

Reference:

### GENMAC Daily-GAS RG4700HS NG SINGLE-PHASE GENERATOR 5,3KVA

The generator Genmac Daily-GAS RG4700HS NG single-phase is equipped with a Honda engine powered by methane gas capable of delivering a power of 5,3KVA with capacitor voltage regulator (AVR optional).

Genmac silenced professional high quality natural generator with 5,3KVA power produced. Genmac is equipped with an oversized air-cooled Honda engine.

Genmac professional methane generators are highly reliable machines, built with quality components to be used in the professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Honda engines are built using the best materials, the most innovative techniques and the most advanced methods for quality control.

Each engine is thoroughly tested in order to prove its perfect functioning before delivery.

In case of need, Honda's assistance service is always at your disposal.

The 5,3KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

### AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

### TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily-GAS RG4700HS NG 5,3KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: Methane gas

Firing: Electric

Phase type: Single phase

Continuous power: 4.8KVA / 4.9KW

Maximum power: 5.3KVA / 4.8KW

Motor: Honda GX390

Socket panel: 1 x 16A 230V / 2 x 32A 230V

Voltage: 230V  
Frequency: 50 Hz  
3000 rpm  
Autonomy @ 75%: 1.7 h fixed rpm  
Acoustic pressure: 63 db (A) @ 7m  
Length (mm): 1030  
Width (mm): 620  
Height (mm): 804  
Dry weight (Kg): 183

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4.8
Continuous power single phase (KW)	4.3
Maximum power single phase (KVA)	5.3
Continuous power single phase (KVA)	4.8
Fuel	Natural Gas
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 16A 230V / 2 x 32A 230V
Engine	Honda GX390
Engine rpm (rpm)	3000
Starting system	Elettrico
Cooling	Air
Poles	2
Consumption (L/h)	1.79
Acoustic pressure	63 dB(A) a 7 m
Length (mm)	1030
Width (mm)	620
Height (mm)	804
Dry weight (Kg)	183
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS

---

Voltage regulator

AVR (optional)

---

Engine manufacturer

Honda

---