

EGM RP10000-SE GENERATOR 8KW



Reference: RP10000-SE

EGM RP10000-SE THREEPHASE GENERATOR 8KW

The generator EGM RP10000-SE threephase is equipped with a gasoline engine capable of delivering 8KW power with optional AVR voltage regulator.

The RP10000-SE threephase EGM generator provides reliable power for home, work and leisure environments Safe powering of home appliances and other electronic devices Outdoor party solution.

The generator is easy to install and operate, as simple as starting and stopping with clear and intuitive controls (Manual / Elettric start) Auto power off for low oil level Durable chassis.

The 8KW threephase generator is equipped with bolted, heavy duty wheels and hinged handle make it a robust and easy to transport. The recessed sockets with snap-on safety covers make it more secure.

The generator has a practical double-curved handle, which can be folded down for easy mobility and storage. EGM RP10000-SE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the OHV engine that allows to deliver a maximum power of 8KW.

The AVR is indispensable to make the generator work at its best, it all needs an electronic control system, an AVR, which guarantees the good functioning of the machine and of the electrical network behind it.

TECHNICAL CHARACTERISTICS OF THE THREEPHASE GENERATOR EGM RP10000-SE 8KW

Phase Type: Three Phase
Maximum Output: 8KW
Continuous Output: 7.5KW
Stationary: Fixed
Power supply: Gasoline
Starting: Manual / Electric
Displacement: 459 cc
Voltage: 400 V
Frequency: 50 Hz
Autonomy at 50% load: 9 h
Tank capacity: 25l
Sound power: 97 dB(A) @ 7m
Automatic voltage regulation: AVR
Length (mm): 700
Width (mm): 526
Height (mm): 580
Dry weight (Kg): 102

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

Technical Sheet

Phase	Three phase
Maximum power single phase (KW)	8
Continuous power single phase (KW)	7.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	400
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Starting system	Manual / Electric
Poles	2
Acoustic pressure	97 dB(A) @ 7m
Length (mm)	700
Width (mm)	526
Height (mm)	580
Dry weight (Kg)	102
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR