



## EGM ISB3500-SE GENERATOR 3,8KW

Reference: ISB3500-SE

### EGM ISB3500-SE SINGLEPHASE GENERATOR 3,8KW

The generator EGM ISB3500-SE singlephase is equipped with a gasoline engine capable of delivering 3,8KW power with optional AVR voltage regulator.

The ISB3500-SE singlephase EGM generator provides reliable power for home, work and leisure environments Safe powering of home appliances and other electronic devices Outdoor party solution.

The generator is easy to install and operate, as simple as starting and stopping with clear and intuitive controls (Manual start) Auto power off for low oil level Durable chassis.

The 3,8KW singlephase generator is equipped with bolted, heavy duty wheels and hinged handle make it a robust and easy to transport. The recessed sockets with snap-on safety covers make it more secure.

The generator has a practical double-curved handle, which can be folded down for easy mobility and storage. EGM ISB3500-SE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the OHV engine that allows to deliver a maximum power of 3,8KW.

The Inverter voltage regulator is essential to make the generator work at its best, in fact it needs an electronic control system, an Inverter in fact, which ensures the proper functioning of the machine and the electrical network underlying it.

#### TECHNICAL CHARACTERISTICS OF THE SINGLEPHASE GENERATOR EGM ISB3500-SE 3,8KW

Phase Type: Single Phase  
Maximum Output: 3.8KW  
Continuous Output: 3.5KW  
Stationary: Fixed  
Power Supply: Gasoline  
Starting: Manual / Electric  
Displacement: 223 cc  
Voltage: 230 V  
Frequency: 50 Hz  
Autonomy at 50% load: 10 h  
Tank capacity: 10l  
Acoustic power: 58 dB(A) @ 7m  
Automatic voltage regulation: Inverter  
Length (mm): 660  
Width (mm): 560  
Height (mm): 650  
Dry weight (Kg): 45

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.8
Continuous power single phase (KW)	3.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Starting system	Manual / Electric
Poles	2
Acoustic pressure	58 dB(A) at 7 m
Length (mm)	660
Width (mm)	560
Height (mm)	650
Dry weight (Kg)	45
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	Inverter