



## EGM ISB8000-SE GENERATOR 7,5KW

Reference: ISB8000-SE

### EGM ISB8000-SE SINGLEPHASE GENERATOR 7,5KW

The generator EGM ISB8000-SE singlephase is equipped with a gasoline engine capable of delivering 7,5KW power with optional AVR voltage regulator.

The generator is easy to install and operate, as simple as starting and stopping thanks to clear and intuitive controls (manual / electric / remote start) Auto power off for low oil level Resistant chassis. The generator is complete with electric and remote starting control unit

The 7,5KW single-phase generator is equipped with bolted, heavy duty wheels and hinged handle to make it a robust and easy to carry. The recessed sockets with snap-on safety covers make it safer.

The 7,5KW singlephase generator is equipped with bolted, heavy duty wheels and hinged handle make it a robust and easy to transport. The recessed sockets with snap-on safety covers make it more secure.

The generator has a practical double-curved handle, which can be folded down for easy mobility and storage. EGM ISB8000-SE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the OHV engine that allows to deliver a maximum power of 7,5KW.

#### TECHNICAL CHARACTERISTICS OF THE SINGLEPHASE GENERATOR EGM ISB8000-SE 7,5KW

Phase type: Single-phase  
Maximum output: 7.5KW  
Continuous output: 7KW  
Stationary: Fixed  
Power supply: Gasoline  
Starting: Manual / Electric  
Displacement: 459 cc  
Voltage: 230 V  
Frequency: 50 Hz  
Run time at 50% load: 10.5 h  
Tank capacity: 26l  
Acoustic power: 63 dB(A) @ 7m  
Automatic voltage regulation: Inverter  
Length (mm): 730  
Width (mm): 610  
Height (mm): 730  
Dry weight (Kg): 115

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.5
Continuous power single phase (KW)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Starting system	Manual / Electric
Poles	2
Acoustic pressure	63 dB(A) at 7 m
Length (mm)	730
Width (mm)	610
Height (mm)	730
Dry weight (Kg)	115
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	Inverter