

GENMAC DAILY G6500YS-M5 GENERATOR 6,9KVA



Reference:

GENMAC DAILY G6500YS-M5 THREE-PHASE GENERATOR 6,9KVA

The generator Genmac Daily G6500YS-M5 three phase is equipped with a Yanmar L100 Stage V motor powered by diesel capable of delivering a power of 6,9KVA with capacitor voltage regulator (AVR optional).

The Genmac Daily G6500YS-M diesel generator is equipped with an oversized air-cooled Yanmar motor. Genmac Daily G6500YS-M professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

The Stage V engine allows the use of the generator set also for mobile use, for example for road construction sites and rental services. The generator is suitable for applications in different contexts such as: hospitals, industries, shopping centers, hotels, airports, banks, universities, stadiums, offices, etc..

All Yanmar engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.

In case of need, Yanmar service is always at your disposal.

The Genmac Daily G6500YS-M generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.

The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily G6500YS-M5 6,9KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: Diesel

Starting: Electric

Phase type: Singlephase / Threephase

Singlephase continuous Output: 1.9KVA / 1.5KW

Maximum SinglePhase Output: 2.3KVA / 1.9KW

Continuous ThreePhase Output: 5.6KVA / 4.5KW

Maximum ThreePhase Output: 6.9KVA / 5.6KW
 Motor: Yanmar L100
 Emissions Standard: Stage V
 Receptacle panel: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
 Voltage: 230 / 400 V
 Frequency: 50 Hz
 3000 rpm
 Tank capacity: 19 l
 Autonomy @ 75%: 15 h fixed revolutions
 Sound pressure @7m: 67 dBa
 Length (mm): 1030
 Width (mm): 620
 Height (mm): 804
 Dry weight (Kg): 203

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	1.9
Continuous power single phase (KW)	1.5
Maximum power single phase (KVA)	2.3
Continuous power single phase (KVA)	1.9
Maximum power three phase (KW)	5.5
Continuous power three phase (KW)	4.5
Maximum power three phase (KVA)	6.9
Continuous power three phase (KVA)	5.6
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
Engine	Yanmar L100, 4 stroke
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Cooling	Air
Poles	2
Fuel tank capacity (L)	19
Running time (h)	

Acoustic pressure	67 dB(A) at 7 m
Length (mm)	
Width (mm)	620
Height (mm)	
Dry weight (Kg)	203
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Yanmar