

GENMAC DAILY G7000KS-M5 GENERATOR 7,0KVA



Reference:

GENMAC DAILY G7000KS-M5 THREE-PHASE GENERATOR 7,0KVA

The generator Genmac Daily G7000KS-M5 three phase is equipped with a Kohler KD15-440 Stage V motor powered by diesel capable of delivering a power of 7,0KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced three-phase diesel power generator, Genmac with 7,0KVA power. The Genmac diesel generator is equipped with an oversized air-cooled Kohler motor.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

The Stage V engine allows the use of the generator set also for mobile use, for example for road construction sites and rental services. The generator is suitable for applications in different contexts such as: hospitals, industries, shopping centers, hotels, airports, banks, universities, stadiums, offices, etc..

All Kohler engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.
In case of need, Kohler service is always at your disposal.

The 7,0KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.

The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily G7000KS-M5 7,0KVA

Voltage regulator : capacitor (AVR Optional)
Power supply: Diesel
Starting: Electric
Phase type: Singlephase / Threephase
Singlephase continuous Output: 2.1KVA / 1.7KW
Maximum SinglePhase Output: 2.3KVA / 1.9KW

Continuous ThreePhase Output: 6.3KVA / 5.0KW
 Maximum ThreePhase Output: 7.0KVA / 5.6KW
 Motor: Kohler KD15-440
 Emissions Standard: Stage V
 Receptacle Box: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
 Voltage: 230 / 400 V
 Frequency: 50 Hz
 3000 rpm
 Tank Capacity: 19 l
 Autonomy @ 75%: 14 h fixed revolutions
 Sound pressure @7m: 68 dBa
 Length (mm): 1030
 Width (mm): 620
 Height (mm): 804
 Dry weight (Kg): 199

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	1.7
Maximum power single phase (KVA)	2.3
Continuous power single phase (KVA)	2.1
Maximum power three phase (KW)	5.6
Continuous power three phase (KW)	5
Maximum power three phase (KVA)	7
Continuous power three phase (KVA)	6.3
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
Engine	Kohler KD 15-440
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Cooling	Air
Poles	2
Fuel tank capacity (L)	19
Running time (h)	14
Acoustic pressure	68 dB(A) at 7 m

Length (mm)	
Width (mm)	620
Height (mm)	
Dry weight (Kg)	199
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Kohler
