



BA.M.E. MEC80 MOTOR 0,75KW 2 POLES

Reference: MEC80075-2 B3

BA.M.E. MEC80 0,75KW 2 POLES SINGLE PHASE ASYNCHRONOUS ELECTRIC MOTORS

The BAME MEC80 electric motor is capable of delivering a power of 0,75KW, asynchronous single-phase closed construction with protection class IP54.

BA.M.E MEC80 is an asynchronous AC motor in which the angular speed of the rotor is lower than the rotation speed of the magnetic field generated by the stator windings, hence the asynchronism (as opposed to the synchronous motor, in which the rotor speed is a direct function of the stator field generation frequency).

The BA.M.E. motor features a closed design with IP54 protection class which ensures that the unit is protected from dust accumulation inside and splash water from any direction, making it incredibly safe and can be used in many areas without fear of water.

The BA.M.E. MEC80 motor with a power of 0,75KW has different constructive forms, in order to be as versatile as possible and to be adapted to any use.

The BA.M.E. motor is with continuous duty or S1 which allows the motor to continue to work even under constant load remaining in thermal equilibrium, which makes it particularly efficient even with heavy loads, without the fear of malfunctions or overvoltages that may compromise its operation.

BA.M.E. MEC80 is complete with a capacitor essential for starting and running. Thanks to the capacitor the current on one or more windings is altered to create a rotating magnetic field which leads to the rotation of the motor shaft.

TECHNICAL FEATURES ELECTRIC MOTOR BA.M.E. MEC80 0,75KW

Motor Type: Electric
Phase: Single-phase
Power: 0,75KW
Mechanical Power: 1 Hp
Voltage: 230 V
Frequency: 50 Hz
Protection: IP54
Length: 284 mm
Width: 160 mm
Height: 200 mm
Weight: 10 Kg

Are you looking for a different model of single phase asynchronous electric motor? Visit the [dedicated](#) section and discover the one that suits your needs.

Images and technical data are not binding.

Technical Sheet

| | |
|-------------------|--------------|
| Phase | Single phase |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 |
| Engine rpm (rpm) | 2800 |
| Poles | 2 |
| Power (KW) | 0.75 |
| Protection degree | IP54 |
| Length (mm) | 284 |
| Width (mm) | 160 |
| Height (mm) | 200 |
| Weight (Kg) | 10 |