



## CGM OKB4-160L

Reference: CGM OK B4-160L /

### CGM OKB4-160L 4 X 160W

CGM OKB4-160L is a fully electric and environmentally friendly light tower, equipped with a battery that allows autonomy for 60 hr of work.

CGM OKB4-160L equipped with 4 projectors capable of delivering a light output of 160W each.

CGM OKB4-160L is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower when opened. The lifting tower is operated electrically and by a hydraulic system that allows maximum extension without effort.

CGM OKB4-160L is equipped with extremely efficient and completely environmentally friendly 2V AGM battery technology, coupled with an inverter that optimizes the voltage supply from the battery pack increasing its life.

#### CGM OKB4-160L TECHNICAL FEATURES

Floodlights: 4 LED 160W  
Illuminated Area: 3000 Mq  
Max Height: 8.5 Mt  
Lift: Hydraulic  
Telescopic pole: Galvanized steel  
Wind Stability: nr 4 stabilizers  
Guides for forklift forks: n.8  
Lumen per luminaire: 20350 lm  
Rotation: 359 degrees  
Voltage: 230V  
Frequency: 50 Hz  
Autonomy with headlights working at 30%: 60 hr  
Battery technology: AGM 2V  
Control technology: Inverter - Onduleur  
Battery pack capacity: 400 Ah  
Number of batteries: 12  
Recharge time: 12 hr  
Expected battery life: 400 cycles  
Width: 1200 mm  
Length: 1130 mm

Height Closed: 2450 mm  
Height Opened: 8500 mm  
Dry weight: 910 Kg

Are you looking for a product with different characteristics? [Here](#) you can find the full range CGM or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Battery type	AGM 2V
Number of batteries	12
Type of lamps	LED
Lamps	4 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	3000
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	359°
Open size (mm)	1200 x 1130 x 8500
Closed size (mm)	1200 x 1130 x 2450
Dry weight (Kg)	910
Super silenced	Yes