



CGM PR4-160L

Reference: PR4-160L /

CGM PR4-160L LED Tower Light

CGM PR4-160L is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

The CGM light tower consists of a trolley with folding handles with safety grips.

CGM PR4-160L is a light tower set up to be combined with a generator of your choice between:

- 6000SP SUPER POWER, with CGM gasoline engine, AVR, 25lt tank
- CX5000 DELUXE with HONDA gasoline engine, AVR, 15lt tank
- DS4000 QUIET with KOHLER diesel engine, AVR, 30lt tank and soundproof enclosure

CGM PR4-160L is equipped with a galvanized steel lifting tower capable of extending up to 5.5 meters maximum height, including 3 feet of stabilization to secure the light tower once opened.

CGM PR4-160L TECHNICAL FEATURES

Floodlights: 4 LED 160W
Illuminated Area: 2200 Mq
Max Height: 5.5 Mt
Lift: Manual
Telescopic pole: galvanized steel
Wind Stability: nr 3 stabilizers
Lumen per luminaire: 20350 lm
Electrical power: 5 KVA / 4.5 KW
Rotation: 355 degrees
Towing trolley: Lento
Forklift guides: nr 2
Power outlet: 16A 230V
Voltage: 230V
Frequency: 50 Hz
Width: 1300 mm
Length: 900 mm
Height Closed: 2160 mm
Height Opened: 5500 mm
Dry weight: 280 Kg

You can find many other different light towers in the [section dedicated](#) to lighting systems.

Images are purely indicative

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A
Type of lamps	LED
Lamps	4 x 160 W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	2200
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Maximum height (m)	5.5
Mast rotation	355°
Open size (mm)	1300 x 900 x 5500
Closed size (mm)	1300 x 900 x 2160
Transportability	Slow Trailer
Dry weight (Kg)	280