



MECC ALTE ECP32-1S/2 C-TYPE THREE PHASE ALTERNATOR 44 KVA AVR

Reference: ECP32-1S/2C SAE3 d6.5

MECC ALTE ECP32-1S/2 C-TYPE THREEPHASE ALTERNATOR 44 KVA DSR

Alternator MECC ALTE ECP32-1S/2 C-TYPE with an output of 44KVA, this unit has a self-exciting and self-regulating Brushless operation equipped with **DSR** voltage regulator.

The alternator ECP32-1S/2 is complete with self-regulation which is achieved by means of a digital electronic regulator powered by an auxiliary winding.

The MECC ALTE ECP32-1S/2 alternator is ruggedly designed to meet industry requirements and the most demanding technological specifications needed in various applications. They are available as a bearing in single or double bearing configuration. To couple them to a main engine, you can choose from a wide range of flanges and fittings.

The MECC ALTE ECP32-1S/2 alternator consists of a fixed stator with slotted slots and a rotating inductor. In addition, models above 15 KVA are equipped with a damping cage as standard. All alternator windings have a 2/3 pitch in order to reduce harmonic content.

MECC ALTE ECP32-1S/2 alternators comply with Italian standard CEI 2-3 file 11111. This standard corresponds to the European EN 60034-1 and the international IEC 60034-1, is linked to the British BS 4999 Part 101, is equivalent to the German VDE 0530 Part 1 and is included in the French NF 51.111.

TECHNICAL FEATURES MECC ALTE ALTERNATOR ECP32-1S/2 C-TYPE

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Output:

(50Hz) 29 KVA / 29 KW

(60Hz) 35 KVA / 35 KW

Single Phase Continuous Output:

(50Hz) 26.4 KVA / 26.4 KW

(60Hz) 31.7 KVA / 31.7 KW

Maximum three-phase output:

(50Hz) 44 KVA / 35.2 KW

(60Hz) 53 KVA / 42.4 KW

ThreePhase Continuous Output:

(50Hz) 40 KVA / 32 KW

(60Hz) 48 KVA / 38.4 KW

Frequency: 50 / 60 Hz

Voltage: 230 / 400 V

Degree of Protection: IP23

Alternator revolutions: 3000 rpm

Number of Poles: 2

Efficiency: 87.4%
Width: 542.7 mm
Length: 613.5 mm
Height: 542.7 mm
Weight: 173 Kg
Constant speed alternator
Brushless
Voltage regulator: AVR

Looking for a product with different features? [Here](#) you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	29 (50Hz) - 35 (60Hz)
Continuous power single phase (KW)	26.4 (50Hz) - 31.7 (60Hz)
Maximum power single phase (KVA)	29 (50Hz) - 35 (60Hz)
Continuous power single phase (KVA)	26.4 (50Hz) - 31.7 (60Hz)
Maximum power three phase (KW)	35.2 (50Hz) - 42.4 (60Hz)
Continuous power three phase (KW)	32 (50Hz) - 38.4 (60Hz)
Maximum power three phase (KVA)	44 (50Hz) - 53 (60Hz)
Continuous power three phase (KVA)	40 (50Hz) - 48 (60Hz)
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Engine rpm (rpm)	3000
Poles	2
Single-phase power (KVA)	35
Three-phase power (KVA)	53
Efficiency (%)	88.9
Protection degree	IP23
Acoustic pressure	77 dB(A) at 7 m
Length (mm)	658
Width (mm)	392
Height (mm)	606
Dry weight (Kg)	173
Brushes	No
PMG	No
Type of alternator	Constant Speed

Voltage regulator	AVR
Weight (Kg)	225
