



## MECC ALTE ECP34-2S/2 THREE PHASE ALTERNATOR 125 KVA AVR

Reference: ECP34-2S/2 SAE3 d11.5

### MECC ALTE ECP34-2S/2 THREEPHASE ALTERNATOR 125 KVA DSR

Alternator MECC ALTE ECP34-2S/2 threephase with a power of 125KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with voltage regulator **DSR**.

The MECC ALTE ECP34-2S/2 alternators are self-regulating, 2-pole brushless. They are equipped with a rotating inductor provided with a damping cage and a fixed armature with inclined slots. The windings have a shortened pitch to reduce the harmonic content.

Tests for electromagnetic compatibility have been carried out in compliance with the conditions prescribed by the standards, with the neutral connected to earth. Executions in accordance with other specifications can be carried out at the customer's request.

The mechanical structure of the ECP34-2S/2 alternator, which is always very robust, allows easy access to the connections and enables the various components to be checked just as easily. The casing of the MECC ALTE is in cast iron, the shaft in C45 steel with splined fan. The degree of protection is IP23 (a higher degree of protection is possible on request).

The high quality bi-component insulating resin used by Mecc Alte ECP34-2S/2, is a polyester specially developed for use in vacuum or dip and drip impregnation machines. It has superior adhesion strength characteristics, high chemical and humidity resistance and is suitable for use up to 212° C.

The ECP34-2S/2 alternators conform to the Italian CEI 2-3 file 11111 . This corresponds to the European EN 60034-1 and the international standard IEC 60034-1, is linked to the British BS 4999 Part 101, is equivalent to the German VDE 0530 Part 1 and is included in the French NF 51.111.

#### TECHNICAL FEATURES MECC ALTE ALTERNATOR ECP34-2S/2

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Output:

(50Hz) 83KVA / 83KW

(60Hz) 99KVA / 99KW

Continuous SinglePhase Output:

(50Hz) 74.6KVA / 74.6KW

(60Hz) 89.1KVA / 89.1KW

Maximum threephase output:

(50Hz) 125KVA / 100KW

(60Hz) 150KVA / 120KW

Continuous threephase output:

(50Hz) 113KVA / 90.4KW

(60Hz) 135KVA / 108KW

Frequency: 50 / 60 Hz

Voltage: 230 / 400 V  
 Degree of protection: IP23  
 Alternator revolutions: 3000 rpm  
 Number of poles: 2  
 Efficiency: 90.7%  
 Width: 417 mm  
 Length: 817.5 mm  
 Height: 743 mm  
 Weight: 403 kg  
 Constant speed alternator  
 Brushless  
 Voltage regulator: AVR

Looking for a product with different features? [Here](#) you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

## Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	83 (50Hz) - 99 (60Hz)
Continuous power single phase (KW)	74.6 (50Hz) - 89.1 (60Hz)
Maximum power single phase (KVA)	83 (50Hz) - 99 (60Hz)
Continuous power single phase (KVA)	74.6 (50Hz) - 89.1 (60Hz)
Maximum power three phase (KW)	100 (50Hz) - 120 (60Hz)
Continuous power three phase (KW)	90.4 (50Hz) - 108 (60Hz)
Maximum power three phase (KVA)	125 (50Hz) - 150 (60Hz)
Continuous power three phase (KVA)	113 (50Hz) - 135 (60Hz)
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Engine rpm (rpm)	3000
Poles	2
Single-phase power (KVA)	99
Three-phase power (KVA)	150
Efficiency (%)	90.7
Protection degree	IP23
Acoustic pressure	77 dB(A) at 7 m
Length (mm)	417
Width (mm)	817.5
Height (mm)	743
Dry weight (Kg)	403
Brushes	No

---

PMG	No
Type of alternator	Constant Speed
Voltage regulator	AVR
Weight (Kg)	225

---