



HELVI fastDARK WELDING MASK

Reference: 21905116

HELVI fastDARK WELDING MASK

HELVI fastDARK is a welding mask that offers optimal face protection by giving the possibility of adjustments according to one's needs.

To offer maximum protection HELVI fastDARK gives the user the possibility to adjust:

- **delay time:** you can adjust the time it takes for the filter to become transparent again once the welding is finished. You can choose a time ranging from 0.1 to 1.0 second .
- **sensitivity:** you can adjust the sensitivity to ambient light.
LO (low) = not very sensitive to light.
HI (high) = very sensitive to light. This setting is ideal for welding at low currents and for welding in dimly lit environments.
You can adjust the sensitivity to ambient light.

TECHNICAL FEATURES HELVI tigMAKER 210HF Pulse

Optical Class: 1/1/1/2
Filter Size: 110 x 90 x 9 mm
Visual: 92 x 42 mm
Sensors: 2
Light Level: 4. 0
Darkening degree: 9-13
Moling: YES
Protection adjustment: External. variable degree
UVIR protection: up to DIN 16
Light to dark time: 1/25000 s
Dark to light time: 0. 1 - 1.0 s
Sensitivity/Delay: Continuously adjustable
Power supply: Solar cells and 1 CR2032 battery
ON/OFF: Automatic
Low battery alarm: Yes, red light
Minimum Amp/TIG setting: >10A AC - DC

Looking for a Welding Mask with different features? [Here](#) you can find the whole range of HELVI or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

Technical Sheet

Motor insulation class	H
Length (mm)	210
Width (mm)	220
Height (mm)	310
Weight (Kg)	