

MOSA GE 225 FXC

Reference: MOSA - Morsettiera-GE 225 FXC



MOSA GE225 FXC 176KW Generator

MOSA GE225 FXC is a three-phase generator with an IVECO FPT N67 TM7 diesel engine capable of delivering a maximum power of 176KW. The MOSA GE225 FXC generator set is equipped with electric start. The MOSA GE225 FXC generator set alternator is synchronous, three-phase, self-excited, self-regulated, brushless with class H insulation with AVR voltage regulator. MOSA GE225 FXC is compact and easy to maneuver and transport thanks to its compact size, with a weight of 2160 Kg as well as the practical pierceable base. The MOSA Generator with 230 liters fuel tank has a fuel consumption of 34 liters/hour at 75% of the load for a range of more than 9 hours.

MOSA GE225 FXC Technical Specifications:

NOMINAL OUTPUT POWER

Three-phase Stand-by power: 220 kVA (176 kW) / 400V / 317.5A

Three-phase PRP power: 200 kVA (160 kW) / 400V / 288.7A

Three-phase COP power: 165 kVA (132 kW) / 400V / 238.2A

Frequency: 50 Hz

MOTOR DATA

Model: IVECO FPT N67 TM7

Net standby output 194 kW (264 hp)

Net PRP output 176.5 kW (240 hp)

Net COP output 141.5 kW (192.5 hp)

Cylinders / Displacement 6/ 6700 cm³ (6.7 lit.)

Bore / Stroke 104 / 132 (mm)

Compression ratio 17.5 : 1

BMEP (Effective Average Pressure: 2332 kPa - 2116 kPa

RPM Controller: Mechanical

110 % (Standby Power): 49 lit./h

100 % PRP: 42.1 lit./h

75 % PRP: 37.3 lit./h

50 % PRP: 24 lit./h

GENERAL SPECIFICATIONS

Tank capacity: 230 lt.

Autonomy (75% of PRP): 6 h

Measured acoustic power LwA: 95 dB(A) (70 dB(A) @ 7m)

Guaranteed acoustic power LwA: 97 dB(A) (72 dB(A) @ 7m)

Width: 3400 mm

Length: 1200 mm

Height: 1800 mm

Dry weight: 2210 kg

If you are looking for another product such as MOSA GE225 FXC generator set then you can browse our catalog for more [land based generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	176
Continuous power three phase (KW)	160
Maximum power three phase (KVA)	220
Continuous power three phase (KVA)	200
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	FPT (IVECO) NEF67TM7
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	6
Number cylinders	6
Oil capacity (L)	17
Cooling	Water
Inyección	Direct
Alternator	Three-phase synchronous self-excited, self-regulated, brushless
Bore x stroke (mm)	104 x 132
Fuel tank capacity (L)	230
Consumption (L/h)	37 at 75% of the load
Running time (h)	6 at 75% of the load
Acoustic power	95 dB(A)
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1200
Height (mm)	1800

Dry weight (Kg)	2210
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco
