



## MOSA TF NM9 L-4x350 LED Lighting Tower

Reference: C01000G0

### MOSA TF NM9 L-4x350 LED Light Tower

MOSA TF NM9 L-4x350 is a lighting tower equipped with 4 halogen lamps 350 W, provides a high illuminated area of over 4800 square meters.

MOSA TF NM9 L-4x350 are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

Among the most characteristic elements is the upper protection of the telescopic pole, a MOSA exclusive, which safeguards one of the most delicate points of the entire MOSA TF NM9 L-4x350 from atmospheric agents, building site waste, dust and leaves.

MOSA TF NM9 L-4x350 is essentially composed of:

- a supporting frame or base on which the generating set is fixed
- four height-adjustable stabilizers, two of which are extendable, to guarantee the stability of the tower on any working surface
- a single-axle, slow-moving towing trolley with wheels and mudguards, complete with drawbar and height-adjustable parking foot
- a telescopic pole with manual lifting, vertical elevation with maximum working height of 9 meters and manual rotation of 340°.
- an electrical panel and power cable, complete with all the protection, command and control devices required for a simple and safe use of the lighting tower.

Thanks to the lateral handles, placed at the base of the pole, it is possible to direct the light beam of the floodlights according to the needs, acting in the following two ways

- by adjusting the inclination of each floodlight

The safety stop stops the descent at a safe height that avoids the risk of collisions with the floodlights during the normal descent phase or in the event of sudden breakage of the telescopic cables or the automatic brake of the lifting winch.

#### TECHNICAL CHARACTERISTICS MOSA TF NM9 L-4x350

Maximum height (mt.): 9

Lift: Manual

Lit area: 4800 m<sup>2</sup>

Lamps: LED

Lamps: 4 x 350 W

Transportability: Slow Towing Trolley

Dry weight (Kg): 800

Dimensions Min. (mm): 3920x1410x2240

Max. (mm): 3920x1975x9000

Wind stability (Km/h): 80

Pole rotation: 340°

Frame designed for coupling with single-phase power generators from 8 to 20 KVA

Looking for a light tower with different characteristics? [Here](#) you can find the entire range Mosa or other brands specializing in the field.

The images are purely indicative.

## Technical Sheet

Type of lamps	LED
Lamps	4 x 350 W
Telescopic pole	Galvanized
Illuminated area (m <sup>2</sup> )	4800
Total lumens (Lm)	223820
Lifting System	Manual lifting system
Maximum height (m)	9
Mast rotation	340°
Open size (mm)	3920x1975x9000
Closed size (mm)	3920x1410x2240
Stability to wind (Km/h)	80 Km/h
Dry weight (Kg)	800
Brushes	No
Feed Type	Single-Phase