



AURORA TOWER LIGHT BETA B-L4X160-F

Reference: BETA B-L 4X160 - F

AURORA TORRE FARO BETA B-L4X160-F

AURORA BETA B-L4X160-F is a light tower produced by Green Power completely electric and ecological, equipped with a battery that allows the autonomy for 60 hours of work.

AURORA BETA B-L4X160-F is equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA BETA B-L4X160-F is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting tower is operated electrically and by a hydraulic system that allows maximum extension without effort.

AURORA BETA B-L4X160-F is powered by a battery pack making it extremely efficient and quiet. The battery operation of the light tower makes it completely ecological, in addition it is equipped with a special inverter that optimizes the supply of voltage from the battery pack increasing its life.

The lenses of the AURORA light tower are equipped with extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA BETA tower can cover an area of 3300 m², ensuring a brighter, safer and more productive site.

The light tower AURORA BETA B-L4X160-F is equipped with a homologated trolley complete with rear lights with integrated reverse light and all the features for a correct urban and extra-urban transport.

TECHNICAL FEATURES AURORA BETA B-L4X160-F

Manufacturer: Green Power
Floodlights: 4 LED 160W
Illuminated Area: 3300 Mq
Max Height: 8.5 Mt
Lift: Hydraulic
Telescopic pole: Galvanized steel
Wind Stability: nr 4 stabilizers
Transport: trolley
Lumen per luminaire: 40700 lm
Voltage: 230V
Frequency: 50 Hz
Power supply: Batteries
Autonomy 30% load: 60 hr
100% recharge: 12 hr

Looking for a product with different features? [Here](#) you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Starting system	Electric
Type of lamps	LED
Lamps	4 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	3300
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	359°