



AURORA LIGHT TOWER ALPHA K2-L 4X320 - S WITH SLOW TOWING TROLLEY

Reference: ALPHA K2-L 4X320 - S

AURORA LIGHT TOWER ALPHA K2-L 4X320 - S WITH SLOW TOWING TROLLEY

AURORA ALPHA K2-L 4X320 - S is a light tower with generator equipped with Kohler 15LD350 Diesel engine and manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA ALPHA K2-L 4X320 - S is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows maximum extension without effort.

AURORA ALPHA K2-L 4X320 - S comes with Kohler 15LD350 engine, this engine is super efficient with 3000 rpm. The AURORA ALPHA light towers in addition guarantee you an autonomy of 180 h of work at 30% of the load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA tower can cover an area of 5000 m², ensuring a brighter, safer and more productive site. AURORA ALPHA K2-L 4X320 - S comes complete with a slow moving trolley, which gives the customer the ability to easily transport the light tower.

TECHNICAL CHARACTERISTICS AURORA ALPHA K2-L 4X320 - S

Manufacturer: Green Power
Projectors: 4 320W LEDs
Lighted Area: 5000 Sq Ft
Max Height: 8.5 Mt
Rise: Manual
Motor: Kohler 15LD350
Emissions: Stage V
Power supply: Diesel
Engine speed: 3000 rpm
Telescopic pole: Galvanized steel
Wind resistance max: 100 Km/h
Wind stability: nr 4 stabilizers
Transport: Slow towing
Noise level at 7 mt: 70 dB (A)
Total lumens: 166200 lm
Voltage: 230V
Frequency: 50 Hz
Autonomy 30% load: 180 hr
Closed dimensions: 1154x1118x2430 mm
Open dimensions: 2030x2202x8500 mm

Dry weight: 560 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Type of lamps	LED
Lamps	4 x 320W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	5000
Total lumens (Lm)	166200
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	350°
Open size (mm)	2030x2202x8500 mm
Closed size (mm)	1154x1118x2430 mm
With generator / Without generator	With generator
Transportability	Slow Trailer
Stability to wind (Km/h)	100 Km/h
Dry weight (Kg)	560
Engine manufacturer	Kohler 15LD350