



## AURORA LIGHT TOWER ALPHA K2-L 4X320 - F WITH FAST TOWING TROLLEY

Reference: ALPHA K2-L 4X320 - F

### AURORA LIGHT TOWER ALPHA K2-L 4X320 - F WITH FAST TOWING TROLLEY

AURORA ALPHA K2-L 4X320 - F is a light tower with generator equipped with Kohler 15LD350 Diesel engine and manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA ALPHA K2-L 4X320 - F is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows maximum extension without effort.

AURORA ALPHA K2-L 4X320 - F comes with Kohler 15LD350 engine, this engine is super efficient with 3000 rpm. The AURORA ALPHA in addition guarantee you an autonomy of 180 h of work at 30% of the load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA tower can cover an area of 5000 m<sup>2</sup>, ensuring a brighter, safer and more productive site. AURORA ALPHA K2-L 4X320 - F is supplied complete with fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for proper urban and extra-urban transport.

#### TECHNICAL CHARACTERISTICS AURORA ALPHA K2-L 4X320 - F

Manufacturer: Green Power  
Projectors: 4 320W LEDs  
Lighted Area: 5000 Square Meter  
Max Height: 8.5 Mt  
Lift: Manual  
Engine: Kohler 15LD350  
Emissions: Stage V  
Power supply: Diesel  
Engine speed: 3000 rpm  
Telescopic pole: Galvanized steel  
Wind resistance max: 100 Km/h  
Wind stability: nr 4 stabilizers  
Transport: Fast towing trolley  
Noise level at 7 mt: 70 dB (A)  
Total lumens: 166200 lm  
Voltage: 230V  
Frequency: 50 Hz  
Autonomy 30% load: 180 hr  
Closed dimensions: 1154x1118x2430 mm

Open dimensions: 2030x2202x8500 mm  
Dry weight: 560 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision.

## Technical Sheet

Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Type of lamps	LED
Lamps	4 x 320W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	5000
Total lumens (Lm)	166200
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	350°
Open size (mm)	2030x2202x8500 mm
Closed size (mm)	1154x1118x2430 mm
With generator / Without generator	With generator
Transportability	Fast Trailer
Stability to wind (Km/h)	100 Km/h
Dry weight (Kg)	560
Engine manufacturer	Kohler 15LD350