



AURORA TOWER LIGHT DELTA L 6X160

Reference: DELTA L 6X160 /

AURORA TORRE FARO DELTA L6X160

AURORA DELTA L6X160 is a lighting tower with hydraulic lifting equipped with 6 floodlights capable of delivering a light output of 160W each.

AURORA DELTA L6X160 is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened.

AURORA DELTA L6X160 can be connected in series to other 6 modules allowing you to have a properly illuminated working area for any kind of work you have to do.

The lenses of the AURORA light tower are equipped with an extremely special optic designed specifically for the civil engineering and construction sectors. This innovative, fully directional LED lens design ensures maximized light output and reduced waste.

The safety stop stops the descent at a safe height that avoids the risk of collisions with headlamps during normal descent or in case of sudden breakage of the telescopic cables or the automatic brake of the lifting winch.

AURORA DELTA L6X160 is characterized by extremely compact dimensions and a squared shape that optimize and facilitate its positioning and transport on mobile vehicles. The base, with 4 adjustable and removable anti-tip stabilizers, guarantees a wind stability of 110 Km/h.

TECHNICAL CHARACTERISTICS AURORA DELTA L6X160

Manufacturer: Green Power
Projectors: 6 160W LEDs
Lit Area: 4200 Square meters
Total Lumens: 122100 lm
Max Height: 8.5 Mt
Lift: Hydraulic
Extra sockets: 1 x 16A CEE / 230 V
Pole sections: 6
Manual stabilizers: 4
Lifting hooks: 4
Max wind resistance: 110 Km/h
Fork passage guides: STD
Transportation: Stationary
Voltage: 230V
Frequency: 50 Hz
Contained tower dimensions: 980x1180x2237 mm
Open tower dimensions: 2450x2658x8500 mm

Dry weight: 550 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 16A CEE / 230 V
Starting system	Electric
Type of lamps	LED
Lamps	6 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	4200
Total lumens (Lm)	122100
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	350°
Open size (mm)	
Closed size (mm)	
With generator / Without generator	Without generator
Transportability	Stationary
Dry weight (Kg)	550