



## AURORA TOWER LIGHT LAMBDA 70-L 4X160

Reference: LAMBDA 70-L 4X160

### AURORA LAMBDA 70-L4X160

AURORA LAMBDA 70-L4X160 is a light tower with manual lifting equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA LAMBDA 70-L4X160 is equipped with a galvanized steel lifting tower capable of extending up to 7 meters in maximum height, complete with a Ø80 tripod with retractable legs for ease of use and transport and adjustable feet for use on uneven and rough terrain.

The AURORA tower is complete with a hand pump for raising and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

AURORA LAMBDA 70-L4X160 stands out for its performance, compactness and solidity, with its 4X160W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

AURORA LAMBDA 70-L4X160 does not have a built-in generator set, making it the ideal product for those who already have a power source or grid connection available. With a 36900-lumen beam and 125-degree beam angle, the entire work area will be sufficiently lit for safe and efficient operations. The light tower can operate directly from the wall power supply

The light tower is suitable for a variety of large-scale construction work, maintenance repair, accident management and disaster relief work, high brightness lighting needs.

AURORA LAMBDA 70-L4X160 features extremely compact size and square shape that optimize and facilitate its positioning and transportation on mobile vehicles. The base, with 4 adjustable and removable anti-tip stabilizers, guarantees a wind stability of 80 Km/h.

#### TECHNICAL CHARACTERISTICS AURORA LAMBDA 70-L4X160

Manufacturer: Green Power  
Projectors: 4 160W LEDs  
Lit Area: 2000 Square Meters  
Total Lumens: 81400 lm  
Max Height: 7 Mt  
Rise: Manual  
Pole Sections: 5  
Manual Stabilizers: 4  
Rotation: NO  
Max wind resistance: 80 Km/h  
Transportation: Stationary  
Voltage: 230V

Frequency: 50 Hz  
Contained tower dimensions: 335x335x2039 mm  
Open tower dimensions: 2210x2210x7000 mm  
Dry weight: 120 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

The pictures and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Type of lamps	LED
Lamps	4 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	2000
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Maximum height (m)	7
Open size (mm)	2210x2210x7000
Closed size (mm)	335x335x2039
With generator / Without generator	Without generator
Transportability	Stationary
Dry weight (Kg)	120