



AURORA TOWER LIGHT OMEGA 75-L 4X160 - SF

Reference: OMEGA 75-L 4X160 - SF

AURORA OMEGA 75-L4X160 - SF LIGHTER TOWER

AURORA OMEGA 75-L4X160 - SF is a tower light with manual lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA OMEGA 75-L4X160 - SF is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 7.5 meters. The tower is complete with a hand pump for lifting and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

AURORA OMEGA 75-L4X160 - SF stands out for its performance, compactness and solidity, with its 4X160W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The AURORA OMEGA 75-L4X160 - SF lighting tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units. AURORA OMEGA 75-L4X160 - SF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

One of the most characteristic elements is the upper protection of the telescopic pole, an AURORA exclusive, which safeguards one of the most delicate points of the entire AURORA OMEGA 75-L4X160 - SF from atmospheric agents, building site slag, dust and leaves.

The Aurora light tower is equipped with a fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for a proper urban and extra-urban transport.

TECHNICAL FEATURES AURORA OMEGA 75-L4X160 - SF

Manufacturer: Green Power
Projectors: 4 Led 160W
Lit Area: 3000 Square meters
Total Lumen: 81400 lm
Max Height: 7.5 Mt
Rise: Manual
Pole sections: 4
Rotation: 350°
Max wind resistance: 110 Km/h
Transport: slow towing
Manual stabilizers: 4 + 1
Lifting hooks: 4
Fork passage guides: STD
Useful dimensions of generating set: 720 x 1600 mm
Extra sockets: 1 x 16A CEE / 230 V

Voltage: 230V
Frequency: 50 Hz
Contained tower dimensions: 2125x1202x2335 mm
Open tower dimensions: 3004x1800x7500 mm
Dry weight: 340 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 16A CEE / 230 V
Type of lamps	LED
Lamps	4 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	3000
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Maximum height (m)	7.5
Mast rotation	350°
Open size (mm)	3500x1705x7100
Closed size (mm)	500x1705x2450
With generator / Without generator	Without generator
Transportability	Slow Trailer
Dry weight (Kg)	340