



## AURORA TOWER LIGHT OMEGA 85-L 4X320 - FF

Reference: OMEGA 85-L 4X320 - FF

### AURORA OMEGA 85-L4X320 - FF LIGHTING TOWER

AURORA OMEGA 85-L4X320 - FF is a tower light with hydraulic lifting equipped with 4 floodlights capable of providing a light output of 320W each.

AURORA OMEGA 85-L4X320 - FF is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 8.5 meters. The tower is complete with automatic hydraulic lift.

AURORA OMEGA 85-L4X320 - FF stands out for its performance, compactness and solidity, with its 4X320W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The AURORA OMEGA 85-L4X320 - FF light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units. AURORA OMEGA 85-L4X320 - FF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

AURORA OMEGA 85-L4X320 - FF is equipped with a fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the functions for a correct urban and extra-urban transport.

AURORA OMEGA 85-L4X320 - FF are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

One of the most distinguishing elements is the upper protection of the telescopic pole, an AURORA exclusive, which safeguards one of the most delicate points of the entire AURORA OMEGA 85-L4X320 - FF from atmospheric agents, building site waste, dust and leaves.

#### TECHNICAL CHARACTERISTICS AURORA OMEGA 85-L4X320 - FF

Manufacturer: Green Power  
Projectors: 4 Led 320W  
Lit Area: 5000 Square meters  
Total Lumen: 166200 lm  
Max Height: 8.5 Mt  
Lift: Hydraulic  
Pole sections: 4  
Rotation: 350°  
Max wind resistance: 110 Km/h  
Transportation: fast towing  
Manual stabilizers: 4 + 1  
Lifting hooks: 4  
Fork passage guides: STD  
Useful dimensions generator set: 960 x 1800 mm

Extra sockets: 1 x 16A CEE / 230 V  
Voltage: 230V  
Frequency: 50 Hz  
Contained tower dimensions: 3500x1705x2600 mm  
Open tower dimensions: 3500x1705x8500 mm  
Dry weight: 400 Kg

Are you looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 16A CEE / 230 V
Type of lamps	LED
Lamps	4 x 320W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	5000
Total lumens (Lm)	166200
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	350°
Open size (mm)	3500x1705x8500
Closed size (mm)	3500x1705x2600
With generator / Without generator	Without generator
Transportability	Fast Trailer
Dry weight (Kg)	400