



ULTIMATE130 FIXED UNDERWATER LED SPOTLIGHT

Reference: S00475FX120

ULTIMATE130 FIXED LED UNDERWATER LAMP

ULTIMATE130 FIXED is an underwater LED boat spotlight capable of generating 12000 lumens of light output with remote On/Off control.

The ULTIMATE130 FIXED's internal heat sink can be easily removed for maintenance and upgrades without the hassle of running your boat dry. ULTIMATE130 FIXED has a larger opening that has increased light output by 25%. We recommend installing the light 250mm below the minimum waterline.

With 12000 lumens of light output and a beam angle of 100 degrees, ULTIMATE130 FIXED led is recommended for boats with fiberglass and wood hulls up to 25 meters.

ULTIMATE130 FIXED is recommended for boats over 25 meters, installing each fixture 1-3 meters apart for the best illumination. This flush mount underwater spotlight uses a ULTIMATE130 FIXED screw-in body for installation in GRP, fiberglass hulls.

ULTIMATE130 can be equipped with a wide beam lens, constructed of anodized aluminum and AB2 bronze coated armor. The ULTIMATE130 FIXED underwater spotlight can be supplied in your choice of two configurations: S00475FX120 for 120 V power supply and S00475FX230 for 230 V power supply

TECHNICAL FEATURES ULTIMATE130 FIXED

Hull Material: GRP / Fiberglass
Boat Size: Up to 25m
Spacing: 1m up to 3m
Beam Angle: 100°
Installation Angles: Flush

Lumen: 12000
Kelvin: 7000
Typical LED Life Expectancy: 3000 h
Minimum and Maximum Operating Voltage: 110-240V AC
Current/Amplifier: 1.4 - 0.7 A
Driver Type: External
Output Drivers: N/A
Control Options: On & Off Switch

Device length: 177 mm
Device diameter: 130 mm
Device profile (height): 7.6 mm

Required removal space: 170 mm
Total weight: 4 kg
Cable length: Custom
Cutout hole: 101 mm
Material: Aluminum / Nickel coated / Bronze
Growth resistant lens: Borosilicate glass
Maximum hull thickness: 75 mm

Looking for an Underwater spotlight with different features? [Here](#) you can find the section dedicated to nautical lighting systems with brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Voltage (V)	110-240V AC
Diameter (Ø)	130 mm
Average life of LEDs (hrs)	3000
Type of lamps	LED
Total lumens (Lm)	12000
Length (mm)	177
Weight (Kg)	4
Video	mSzY-vFJivE